

Material Name: Low-VOC Untack Product #: 330793

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

### **Material Name**

Low-VOC Untack

# **Synonyms**

Adhesive Remover / Solvent

#### **Product Use**

Adhesive Remover

#### **Restrictions on Use**

For industrial use only.

### **Manufacturer Information**

Versico 1285 Ritner Highway Carlisle, PA 17013

**USA** 

Phone: +1-800-992-7663

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

### Section 2 - HAZARDS IDENTIFICATION

# Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 3

Skin Sensitization - Category 3

Aspiration Hazard - Category 1

Acute Toxicity - Inhalation - Category 5

Eye Damage - Category 2A

Extremely Flammable Aerosol - Category 1

Specific Target Organ Toxicity (central nervous system) – Category 2

### **GHS Label Elements**

### Symbol(s)









# Signal Word

Danger

# **Hazard Statement(s)**

May cause respiratory irritation. May cause mild skin irritation.

Page 1 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Flammable liquid and vapor.

Contains gas under pressure; may explode if heated

# **Precautionary Statement(s)**

#### **Prevention**

Keep away from heat/sparks/open flames/hot surfaces – no smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Avoid release to the environment.

Use personal protective equipment as required.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.

### Response

Eyes: Contact with eyes may cause irritation. Direct contact with liquid or vapors may cause stinging, tearing, redness, swelling, and eye damage.

Skin: May cause skin irritation and/or dermatitis. Prolonged or repeated contact or exposure to vapors may cause redness, burning, and drying and cracking of the skin.

Inhalation: Breathing high concentrations of vapors may cause irritation of the nose and throat or signs of nervous system depression (i.e. – headache, nausea, drowsiness, dizziness, vomiting, loss of coordination and fatigue).

Ingestion: Ingestion may cause irritation of the digestive tract, nausea, vomiting, and signs of nervous system depression.

### Storage

Rotate stock; use oldest first (FIFO)

Store between 60-90 F

Shelf life expires 1 year from manufacture date

Do not store in direct sunlight

Diminished performance may occur below 60F. If so, warm canister to room temperature. Remove from concrete floor in cold temps.

If frozen, return to room temperature. Some agitation may be required

#### Chronic Effects

Avoid repeated exposure. May cause blood damage. Repeated contact may cause allergic reactions in very susceptible persons.

### **Aggravated Medial Conditions**

Pre-existing eye, skin, or respiratory disorders may be aggravated by exposure to this product.

Page 2 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
67-64-1	Acetone	50 – 75%
98-56-6	Parachlorobenzotrifluoride	22 – 40%
5989-27-5	D-Limonene	1 – 7%

Any remaining ingredients (to comprise 100% of the product) should be considered a proprietary blend of non-hazardous substances, or materials below threshold reporting limits.

### Section 4 - FIRST AID MEASURES

### **Description of Necessary Measures**

### **General Advice**

Show this safety data sheet to the doctor in attendance.

# **Eyes**

Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate medical attention.

### Skin

Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash affected areas thoroughly with mild soap. If skin irritation persists, get immediate medical attention.

### Inhalation

Move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen and get immediate medical attention.

### Ingestion

Do not induce vomiting – seek immediate medical attention. If vomiting occurs, keep head lower than hips to prevent aspiration.

### **Note to Physicians**

Treat symptomatically.

### Section 5 - FIREFIGHTING MEASURES

# **Extinguishing Media**

Carbon dioxide, dry chemicals, foam. Water may be helpful in keeping adjacent containers cool; avoid spreading the liquid with water used for cooling. Water-based sprinkler systems may help contain larger fires.

Page 3 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

# **Special Hazards Arising from the Chemical**

Closed containers may rupture if exposed to fire or extreme heat. May produce toxic fumes if burning.

# **Special Protective Equipment**

Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### Section 6 - ACCIDENTAL RELEASE MEASURES

#### **Personal Precautions**

Use personal protective equipment. Remove all sources of ignition.

### **Environmental Precautions**

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

### Methods for cleaning up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

#### Other Information

None known.

### Section 7 - HANDLING AND STORAGE

### **Precautions for Safe Handling**

Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from extremes of heat or cold. Keep in properly labeled containers.

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Component Exposure Limits**

<b>Hazardous Components</b>	OSHA PEL	ACGIH TLV
Acetone:	1000 PPM	250 PPM
Parachlorobenzotrifluoride	Not established	Not established
D-Limonene	Not established	Not established

Page 4 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

### Individual Protection Measures, such as Personal Protective Equipment

### **Eye/face protection**

Safety goggles or glasses, or full face shield.

### **Skin Protection**

Protective gloves and impervious clothing. Consult the glove/clothing manufacturer for proper selection of materials.

# **Respiratory Protection**

In operations where exposure limits are exceeded, use a NIOSH-approved respirator that has been selected by a technically qualified person for the specific work conditions.

### **Hygiene Practices**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using, do not eat, drink or smoke.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

	Thin, water-		
Appearance	white liquid	Odor	Solvent odor
Odor Threshold	No data	VOC (g/L)	12
VOC (g/L) less exempt & Water	33	Non-volatile (wt%)	0.00
Specific Gravity (g/l)	0.899	Bulk Density (lb/gal)	7.49
Solubility in Water	Insoluble	рН	Not available
Viscosity	Not available	Evaporation rate	Faster than nBuAc
Vapor Pressure (mmHg)	Not available	Vapor Density	Heavier than air
<b>Boiling Point</b>	133.0°F [56.1°C]	Freezing/Melting Point	Not determined
Flammability (solids)	No data	Partition Coefficient (noctonal/water)	No data
<b>Auto-ignition Temp</b>	No data	<b>Decomposition Temp</b>	No data
<b>Explosive Properties</b>	No data	Oxidizing Properties	No data
Flash Point	-4.0°F [-20 °C]	Flammable Limts	Lower: 2.04; Upper: 11.85

Page 5 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

**Other Information** 

No additional information available.

### Section 10 - STABILITY AND REACTIVITY

### **Chemical Stability**

Stable under normal conditions. Hazardous polymerization does not occur

### **Conditions to Avoid**

Keep away from open flames, hot surfaces, static electricity and sources of ignition. Avoid extremes of heat or cold.

### **Materials to Avoid**

Incompatible with strong acids and bases, alkali metals, halogens, and strong oxidizing agents.

### **Hazardous decomposition products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide, smoke, and other unidentified organic compounds may be formed during combustion.

# **Possibility of Hazardous Reactions**

None under normal conditions of use.

### Section 11 - TOXICOLOGICAL INFORMATION

**Reproductive Toxicity:** Acute Toxicity:

No data: No data; Skin: No data; Inhalation: Category 5

Mutagenicity:Irritation:No data.Skin: Category 3STOT-single exposure:Corrosivity:

No data. Corrosivi

STOT-repeated exposure: Sensitisation:

Category 2 Respiratory: No data; Skin: No data

Aspiration Hazard: Typical Routes of Entry:

Category 1 Inhalation, skin absorption, eye contact

ChronicToxicity/Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen. If no ingredients are listed below, then there are no known classifications.

Component IARC NTP OSHA



Material Name: Low-VOC Untack Product #: 330793

### Section 12 - ECOLOGICAL INFORMATION

# **Aquatic Toxicity**

Acute and prolonged Toxicity to Fish: No data Acute Toxicity to Aquatic Invertebrates: No data. Environmental Fate and Pathways: No data Persistence and Degradability: No data Bioaccumulative Potential: No data

Mobility in Soil: No data Other Adverse Effects: No data

### Section 13 - DISPOSAL CONSIDERATIONS

### W aste Disposal Method

Dispose of in accordance with all applicable local, state, and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

# Section 14 - TRANSPORT INFORMATION

### **US DOT Information:**

Shipping Name: CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Acetone,

Parachlorobenzotrifluoride)

Hazard Class: 2.1 UN/NA #: UN3501



# Section 15 - REGULATORY INFORMATION

### **US TSCA**

Yes – All components are listed or exempt.

### **OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Page 7 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

### **SARA 313**

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation Cas No. Weight %

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

Chemical Designation Cas No. Weight %

### **State Regulations**

California Proposition 65

This product contains the following substance(s) known to the state of California to cause cancer or reproductive harm:

Chemical Name CAS Number

### Section 16 - OTHER INFORMATION

# NFPA is a Health, Flammability and Reactivity rating:

Health -1, Fire -3, Reactivity -0

4 -Severe Hazard, 3 – Serious Hazard, 2 – Moderate Hazard, 1 – Slight Hazard, 0 – Minimal

### **Summary of Changes**

New SDS: August 8, 2017

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund

Page 8 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17



Material Name: Low-VOC Untack Product #: 330793

Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### **Other Information**

### **Disclaimer:**

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy his self that the product is entirely suitable for his purposes.

Page 9 of 9 Issue date: 2017-10-19 Revision 1.0 Print date: 2018-01-17