

ASTM C1289 Polyiso Roofing Insulation Classifications

Type II				Type V
				OSB on one side with reinforced felt or glass fiber mat on the other side
Class 1 Glass reinforced felt (GRF) facers on both sides	Class 2 Coated glass (CGF) facers on both sides	Class 4 Coated glass (CGF) facers on both sides (1/2" max thickness)	Class 5 Glass reinforced felt (GRF) facers on both sides	
Available in: Grade 2 (20 PSI) Grade 3 (25 PSI)*	Available in: Grade 2 (20 PSI) Grade 3 (25 PSI)*	Available in: Grade 1 (80 PSI min, 109 PSI max)	Available in: Grade 1 (80 PSI min, 109 PSI max)	Available in: Grade 2 (20 PSI)
InsulBase POLYISO Insulation InsulBase POLYISO Tapered Insulation InsulBase NH POLYISO Insulation InsulBase RL POLYISO RapidLock Insulation	SecurShield POLYISO Insulation SecurShield POLYISO Tapered Insulation SecurShield NH POLYISO Insulation SecurShield RL POLYISO RapidLock (RL) Insulation	SecurShield HD POLYISO Insulation SecurShield HD Plus POLYISO Insulation SecurShield HD Composite POLYISO Insulation SecurShield HD RL POLYISO RapidLock Insulation SecurShield HD Composite RL POLYISO Insulation	InsulBase HD POLYISO Insulation	StormBase POLYISO Insulation

*Grade 3 (25 PSI) is not available for InsulBase RL and SecurShield RL Polyiso