

ASTM C1289 POLYISO ROOFING INSULATION CLASSIFICATIONS

Type II				Type V
				OSB on one side with reinforced felt or glass fiber mat on the other side
<u>Class 1</u> Glass reinforced felt (GRF) facers on both sides	<u>Class 2</u> Coated glass (CGF) facers on both sides	<u>Class 4</u> Coated glass (CGF) facers on both sides (1/2" max thickness)	<u>Class 5</u> Glass reinforced felt (GRF) facers on both sides	
<u>Available in:</u> Grade 2 (20 PSI) Grade 3 (25 PSI)*	<u>Available in:</u> Grade 2 (20 PSI) Grade 3 (25 PSI)*	<u>Available in:</u> Grade 1 (80 PSI min, 109 PSI max)	<u>Available in:</u> Grade 1 (80 PSI min, 109 PSI max)	<u>Available in:</u> Grade 2 (20 PSI)
VersiCore® Insulation VersiCore Tapered Insulation VersiCore NH Polyiso VersiCore RL Polyiso	SecurShield® Insulation SecurShield Tapered Insulation SecurShield RL® Polyiso SecurShield NH Polyiso	SecurShield HD Insulation SecurShield HD Plus Insulation SecurShield HD RL Polyiso SecurShield HD Composite Polyiso SecurShield HD RL Composite	VersiCore HD Polyiso	DuraFaceR® Insulation

* Grade 3 (25 PSI) is not available with VersiCore RL and SecurShield RL Polyiso



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com