Versico Recycling Reference Guide

Need to Recycle Versico Materials from Jobsites?

Post-Consumer Products Recycling Opportunities	Roof Assembly Type	Contact for Recycling	Special Requirements
EPDM Membrane	Ballasted & Mechanically Attached		Membrane
TPO Membrane	Mechanically Attached	nationwidefoam.com 888-820-2764 Repurposed Materials Damon Carson 303-321-1471 damon@repurposedmaterialsinc.com East of Mississippi River: Disposal Alternatives Ron Gluck 617-975-2000 ron@disposalalternatives.net	 No seams, flashings,
PVC Membrane	Mechanically Attached		adhesives or metal
Polyisocyanurate Insulation	Ballasted & Mechanically Attached		 Fold or roll onto a pallet
Expanded Polystyrene Insulation (EPS)	All		puller
Extruded Polystyrene Insulation (XPS)	All		Insulation
Wood Fiber Board	Ballasted & Mechanically Attached		Only full sheets No broken, wet or contaminated boards See reverse side for details
Gypsum Board	Ballasted & Mechanically Attached		
Flexible DASH Dual Tanks, CAV-GRIP® 3V, and CAV-GRIP PVC standard cylinders		See CleanEarth recycling locations on reverse side	12 cylinder min.
CAV-PRIME	New Roofing Installations		26 cylinder min.
Flexible DASH 15-Gallon Drums			9 drum min.
Flexible DASH 50-Gallon Drums			4 drum min.
Large (#85) CAV-GRIP 3V and CAV-GRIP PVC cylinders		434-847-5671 canister@choiceadhesivescorp.com	12 cylinder min.
Ballast	Ballasted	Landscape companies local to the building Vac-it-all.com 800-368-8440	

Other Recycled Materials

Post-Consumer Products Recycling Opportunities	Building Materials Type	Contact for Recycling	
Snap Clad, Tite-Loc, Tite-Loc Plus, Snap-On, PAC 150, PAC T-250, Redi-Roof	Roofs		
PAC-750 Soffit, PAC850 Soffit, Flush Soffit, Reveal Soffit	ffit Soffits Local jobsite municipality recycling facility		
Metal Flush Panels, Reveal Panels, M42/M36 Panels, R36 Panels, 7.2 Panels, 1/2" and 7/8" Corrugated Panels, Precision Series HWP, Highline, Box Rib, Tiles	Walls		







Additional Ways CCM Reduces

Cardboard

Versico Recycling Reference Guide





Membrane Requirements

- Membrane must be flexible and free of contaminants like adhesive, asphalt, facer, fasteners, plates, stones, and mold
- Cut and remove seam overlaps, tapes, flashings and patches
- Fold or roll membrane so it fits squarely on a standard 48" x 40" wooden pallet. Stack membrane to 3' high.
- Secure membrane to the pallet

Insulation Requirements

- Insulation must be full, intact sheets that are dry and free of adhesive, membrane or mold.
- No wet or broken boards
- Stack on dunnage or pallets to 4' high
- Secure insulation by taping the stack together

Non-conforming loads are subject to rejection and surcharge at current disposal rates.

Cylinder and Drum Requirements

- All containers must be empty and placed on a pallet.
- ALL CYLINDERS MUST BE DEPRESSURIZED PRIOR TO SHIPMENT.
 Cylinders that do not have the friable disk or knockout valve punctured will not be accepted.
- Stretch wrap the pallet
- ONLY standard (#40) cylinders of CAV-GRIP 3V, CAV-GRIP PVC, and Flexible DASH Dual Tank or small (#20) cylinders of CAV-PRIME will be accepted at the disposal facility.
- Shipments must contain at least the required minimum quantity or a \$100 fee will be assessed. There is no maximum cap limit for the number of cylinders that can be shipped
- Call the nearest CleanEarth recycling location and arrange shipping

Clean Earth Locations

Address	City/State/Zip	Phone Number
1689 Shar-Cal Road	Calvert City, KY 42029	270-605-2105
1750 Morgantown Industrial Park	Morgantown, WV 26501	304-292-0659
402 Webster Chapel Road	Glencoe, AL 35905	800-739-9156
30677 Huntwood Avenue	Hayward, CA 94544	510-429-1129
1733 Morgan Road	Modesto, CA 95358	510-429-1129
4132 Pompano Road	Charlotte, NC 28216	704-395-9559

 Large (#85) cylinders of CAV-GRIP 3V should be recycled by following the procedure described on the cylinder sticker.



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com