



**Sure-Seal AFX EPDM
Sure-Weld AFX TPO
Sure-Flex KEE HP FleeceBACK
Hot Mopped Adhered Roofing System**

Code Approval Guide

November 2025

Table of Contents

UL Approvals:

Non-Combustible - ANSI UL - Class A.....	2
Combustible - ANSI UL - Class A.....	3

Existing UL Rating Retained:

Combustible and Non-Combustible.....	4
--------------------------------------	---

Mechanically Fastened - Recover

Recover on Steel Decking.....	4
-------------------------------	---

FM Approvals:

Securock New Construction.....	5-6
Securock Recover.....	7
DensDeck Prime New Construction.....	8-9
DensDeck Prime Recover.....	10
HP Recovery Board New Construction.....	11

Reference Notes.....	12
-----------------------------	-----------



Underwriter Laboratories
Hot Mopped (Asphalt) Adhered Roofing System

Non-Combustible- ANSI/UL 790 Spread of Flame Test- Class A

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

System ID	Deck Type	Insulation/Base	Cover Board	Maximum Slope		
				Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
1	Non-Combustible	Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/4" SECUROCK® Gypsum-Fiber Roof Board	2"	1"	Unlimited
2		Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/4" DensDeck Prime Roof Board	2"	1"	Unlimited
3		Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/2" HP Recovery Board	2"	1"	2"
4		One or more layers of the Carlisle Type G2 base sheet, hot mopped or mechanically fastened.	N/A	2"	1"	2"
5	Precast concrete with grouted joints	N/A	N/A	2"	1"	2"
6	Structural (poured-in-place) concrete	N/A	N/A	2"	1"	2"

Underwriter Laboratories
Hot Mopped (Asphalt) Adhered Roofing System

Combustible (1)- ANSI/UL 790 Spread of Flame Test- Class A

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

System ID	Thermal Barrier/Base Sheet	Insulation	Cover Board	Maximum Slope		
				Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
Combustible (1) - ANSI/UL 790 Spread of Flame Test-Class A						
1	N/A	Any UL Classified Carlisle Polyisocyanurate Insulation, any combination, any thickness.	Minimum 1/4" SECUROCK® Gypsum Fiber Roof Board (2)	2"	1"	3"
2	N/A	Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 3/8" SECUROCK® Gypsum Fiber Roof Board (2)	2"	1"	2"
3	N/A	Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/4" DensDeck Prime Roof Board (2)	2"	1"	Unlimited

Underwriter Laboratories
Hot Mopped (Asphalt) Adhered Roofing System

**Existing UL Rating Retained - Non-Combustible or Combustible
(Directly over existing Class A, B or C)**

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Non-Combustible: Steel; St. Concrete; Gypsum; Tectum (Min. 2" thick)

Combustible: 7/16-in. (minimum) thick non-veneer APA-rated sheathing (oriented strand board panels, structural particleboard panels, composite panels or waferboard panels); 15/32-in. (minimum) thick plywood 3/4 in. (minimum) wood; Tectum (less than 2" thick)

System ID	Deck Type	Insulation	Cover Board	Maximum Slope		
				Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
1	Combustible or Non-Combustible	Smooth Asphalt BUR (Type III or IV Asphalt)	N/A	1/2"	1/2"	1/2"
2		Mineral Surfaced Cap Sheet	N/A	1/2"	1/2"	1/2"
3		Modified Bitumen	N/A	1/2"	1/2"	1/2"

Mechanically Fastened Membrane - Recover

Membrane Width	Spacing	Rating	Min. 22 Gauge Grade C Steel (33 ksi)		
			Sure-Seal EPDM	Sure-Weld TPO	Sure-Flex KEE HP
10 Feet	6"	1-105	138293-0-0	138702-0-0	N/A

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Securock- New Construction

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: FAST = Flexible FAST and Flexible FAST Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
FM Approved	Loose laid	Min. 1/4" Securock	12 (2.66 sq. ft)	1-75	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	10 (3.2 sq. ft)	1-90	-	-	389427-0-0
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/4" Securock	10 (3.2 sq. ft) SecurFAST Plate	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 5/8" Securock	8 (4 sq. ft) SecurFAST Plate	1-90	-	-	-
FM Approved	Loose laid	Min. 5/8" Securock	8 (4 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" Securock	8 (4 sq. ft) SecurFAST Plate	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" Securock	6 (5.33 sq. ft) SecurFAST Plate	1-75	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 5/8" Securock	6 (5.33 sq. ft) SecurFAST Plate	1-90	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	20 (1.6 sq. ft)	1-150	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	32 (1 sq. ft)	1-270	-	-	375702-0-0
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	Min. 1/4" Securock	6" ribbons of FAST	1-90	-	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	Min. 1/4" Securock	12" ribbons of FAST	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	18 (1.8 sq. ft.)	Min. 1/4" Securock	6" ribbons of FAST	1-105	-	-	-
Min. 1-1/2" InsulBase Polyiso	24 (1.33 sq. ft.)	Min. 1/4" Securock	4" ribbons of FAST	1-165	-	-	-
Min. 1/2" DensDeck Prime or 5/8" Securock	16 (2 sq. ft.)	Min. 1/4" Securock over 1-1/2" InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Securock- New Construction

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: FAST = Flexible FAST and Flexible FAST Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Steel Deck (Min. 22-Gauge) with SureMB 90 TG or 120 TG Base Torch Applied							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-
Concrete Deck							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" Securock	12" ribbons of FAST	1-270	-	-	-
Min. 1/2" InsulBase Polyiso	Hot Asphalt	Min. 1/4" Securock	Hot Asphalt	1-270	-	-	-
Concrete Deck with VapAir Seal 725TR and Cav-Grip III							
Min. 1-1/2" InsulBase Polyiso	Full-Coverage FAST	Min. 1/4" Securock	12" ribbons of FAST	1-255	-	-	-
Concrete Deck with SureMB 70 SA with Cav-Grip III Primer							
Min. 1-1/2" InsulBase Polyiso	Full-Coverage FAST	Min. 1/4" Securock	12" ribbons of FAST	1-255	-	-	-
Concrete Deck with SureMB 90TG and 120TG Base Torch Applied/Cut-Back Asphalt Primer							
Min. 1-1/2" InsulBase Polyiso	Full-Coverage FAST	Min. 1/4" Securock	12" ribbons of FAST	1-255	-	-	-
Min. 1-1/2" InsulBase Polyiso	Hot Asphalt	Min. 1/2" Securock	Hot Asphalt	1-270	-	-	483488-0-0
Gypsum Deck Tear-Off							
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" Securock	12" ribbons of FAST	1-90	-	-	-
(Celcore) Cellular Lightweight Insulating Concrete Over Steel Decking (Min. 22 Gauge)							
FM Approved	Loose laid	Min. 1/4" Securock	12 (2.67 sq. ft)	1-75	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	10 (3.2 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 5/8" Securock	8 (4 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	20 (1.6 sq. ft)	1-150	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	32 (1 sq. ft)	1-255	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Securock- Recover

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: FAST = Flexible FAST and Flexible FAST Dual Tank

Base Insulation Layer	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Concrete Deck							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" Securock	12" ribbons of FAST	1-90	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing Smooth Asphalt BUR or Modified Bitumen was FM Approved at the time of insulation.

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

DensDeck Prime- New Construction

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: FAST = Flexible FAST and Flexible FAST Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
FM Approved	Loose laid	Min. 1/4" DensDeck Prime	12 (2.67 sq. ft)	1-90	106651-0-0	-	-
FM Approved	Loose laid	Min. 1/2" DensDeck Prime	10 (3.2 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	5/8" DensDeck Prime	8 (4 sq. ft)	1-90	106648-0-0	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" DensDeck Prime	8 (4 sq.ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/4" DensDeck Prime	18 (1.8 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" DensDeck Prime	18 (1.8 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" DensDeck Prime	20 (1.6 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" DensDeck Prime	32 (1 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" DensDeck Prime	32 (1 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 1/2" DensDeck Prime	32 (1 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	-	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	188315-0-0	189734-0-0	375582-0-0
Min. 1-1/2" InsulBase Polyiso	18 (1.8 sq. ft.)	Min. 1/4" DensDeck Prime	6" ribbons of FAST	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	24 (1.33 sq. ft.)	Min. 1/4" DensDeck Prime	4" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	16 (2 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Steel Deck with VapAir Seal 725 TR and Cav-Grip III or 702 Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-
Steel Deck with SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-
Steel Deck with SureMB 90TG or 120TG Base Torch Applied							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/4" DensDeck Prime over InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

DensDeck Prime- New Construction

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: FAST = Flexible FAST and Flexible FAST Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Concrete Deck							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" InsulBase Polyiso	Hot Asphalt	Min. 1/4" DensDeck Prime	Hot Asphalt	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 5/8" DensDeck Prime	8 (4 sq.ft)	1-90	-	210494-0-0	-
Concrete Deck with VapAir Seal 725 TR and Cav-Grip III / 702-LV / 702 Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90 Cav-Grip III	-	-	-
				1-90 702-LV	-	-	-
				1-90 702	-	-	-
Concrete Deck with SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	-	-	-
Concrete Deck with SureMB 90TG and 120TG Base Torch Applied/Cut-Back Asphalt Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	-	-	-
Gypsum Deck Tear-Off							
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	-	-	-
Cellular Lightweight Insulating Concrete Over Steel Decking							
FM Approved	Loose laid	Min. 1/4" DensDeck Prime	12 (2.67 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 1/2" DensDeck Prime	10 (3.2 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 5/8" DensDeck Prime	8 (4 sq. ft)	1-90	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

DensDeck Prime- Recover

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: FAST = Flexible FAST and Flexible FAST Dual Tank

Base Insulation Layer	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Concrete Deck							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 1/4" DensDeck Prime	12" ribbons of FAST	1-90	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing Smooth Asphalt BUR or Modified Bitumen was FM Approved at the time of insulation.

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

HP Recovery Board- New Construction

Membrane Type: Sure-Seal AFX or AFX Plus EPDM Membrane
Sure-Weld AFX or AFX Plus TPO Membrane
Sure-Flex KEE HP FleeceBACK Membrane

Membrane Adhesive: Hot Asphalt

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	Sure-Seal AFX	Sure-Weld AFX	Sure-Flex KEE HP FB
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
FM Approved	Loose laid	Min. 1/2" HP Recovery Board	16 (2 sq. ft)	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	16 (2 sq. ft.)	Min. 1/2" HP Recovery Board	Hot asphalt	1-90	-	325133-0-0	-
Concrete Deck							
Min. 1" InsulBase Polyiso	Hot Asphalt	Min. 1/2" HP Recovery Board	Hot Asphalt	1-300	-	292371-0-0	-
Min. 1" InsulBase Polyiso	Hot Asphalt	Min. 1/2" HP Recovery Board	Hot Asphalt	1-270	292289-0-0	-	-
Concrete Deck with SureMB 90 Base Ply Hot Asphalt attached/Cut-Back Asphalt Primer							
Min. 1" InsulBase Polyiso	Hot Asphalt	Min. 1/2" HP Recovery Board	Hot Asphalt	1-300	-	-	375598-0-0
Cellular Lightweight Insulating Concrete Over Steel Decking							
FM Approved	Loose laid	Min. 1/2" HP Recovery Board	16 (2 sq. ft)	1-90	-	-	-

Hot Mopped (Asphalt) Adhered Roofing System

Reference Notes

1. Any roof covering system listed for use over a combustible roof deck can be installed over a non-combustible roof deck and achieve the same classification.
2. All insulation joints must be staggered a minimum of 6 inches from the deck joints or from the insulation joints directly below.
3. Sure-Seal HP fastener/Sure-Seal Insulation plate.
4. InsulFAST fastener/Sure-Seal Insulation plate.
5. InsulFAST fastener/SecurFAST Insulation Fastening plate.

Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC

(800)-4SYNTEC (800-479-6832)

Sure-Seal AFX or AFX Plus Membrane, Sure-Weld AFX or AFX Plus Membrane,
Sure-Flex KEE HP FleeceBACK Membrane, FleeceBACK and FAST are Trademarks

of Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC

DensDeck Prime is a Trademark of Georgia-Pacific

The contents of this issue represent the applicable information available at the time of publication. The contents of older issues are no longer accurate due to subsequent changes.

2025 Copyright Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC