

# VersiTrim™ Drip Edge



## Overview

Versico's VersiTrim Drip Edge features a 22GA "L" shaped continuous cleat with pre-slotted fastening holes for ease of installing provided fasteners as well as a Kynar® finished cover. It is manufactured in 12' lengths that provide fewer joints/seams and fewer sections to handle for faster installations.

## Features and Benefits

- Variety of face heights available with or without cleat
- Interlocking, concealed splice plates prevents moisture migration
- Manufactured in convenient 12' lengths with pre-punched fastening holes to ensure correct fastener placement
- Factory fabricated miters eliminates the need for field fabrication and provides a cleaner appearance and proper fit
- ANSI/SPRI/FM 4435/ES-1 tested to comply with International Building Code requirements
- Miami-Dade approved to comply with the High-Velocity Hurricane Zone of the Florida Building Code
- Factory Mutual Approved for wind uplift protection

## Installation

For complete installation instructions, refer to Versico specifications and details or visit [www.metalera.com/brands/versico](http://www.metalera.com/brands/versico).

## Finishes

- Natural mill-finish aluminum
- Pre-finished Kynar standard and low gloss
- Premium metallic Kynar
- Anodized aluminum – clear, dark bronze, and black
- Drexlume – Acrylic coated galvalume
- HDG90 Galvanized Steel
- Custom post-painted Kynar finishes available upon request
- Please consult color chart for color and gauge/thickness availability, non stock combinations require minimum order and extended lead time

## Quality Assurance

Tested per ANSI/SPRI/FM 4435/ES-1 Test Methods RE-1 and RE-2 for evaluation of membrane securement strength. Fascia shall be certified by Versico to design pressures as indicated in current edition of ANSI/SPRI ED-1 Design Standard for Edge Systems Used with Low Slope Roofing Systems. Meets International Building Code requirements. Miami-Dade approved to comply with the High-Velocity Hurricane Zone of the Florida Building Code. Factory Mutual Approved for wind uplift protection.

## Technical Services

Engineering and shop drawings, as well as long-form specifications and CAD details, are available from Versico. Product samples, detail sheets, color chips, and color charts are also available for submittal packages. For personal assistance with questions or submittals, contact Versico or your local manufacturer's representative.

## Specifications

|                 |   |
|-----------------|---|
| Face Heights    | 1.25" (Min)<br>10" (Max)  |
| Cover Materials | 24GA Steel<br>0.040" Aluminum<br>0.050" Aluminum<br>0.063" Aluminum |

## Warranty

Versico's VersiTrim Drip Edge is warranted in conjunction with the roofing system, in an edge to edge warranty up to 30 years with 100mph windspeeds.



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • [www.versico.com](http://www.versico.com)