

CARLISLE'S AUTHORIZED APPLICATORS MARKETING ANNOUNCEMENT

ID-2016-03
VapAir Seal™ Flashing Foam
May 17, 2016

To: Carlisle SynTec Systems' Authorized Applicators

Carlisle SynTec Systems is pleased to introduce VapAir Seal™ Flashing Foam, a spray polyurethane foam (SPF) used in conjunction with Carlisle's Air and Vapor Barriers. Flashing Foam allows contractors to seal around penetrations quickly and effectively, creating a seamless, continuous seal that provides insulation and protects against air and vapor infiltration.

Packaged in an easy-to-use, self-contained kit, Flashing Foam can be used on any roof penetration, including pipes and wires. Flashing Foam should be applied around penetrations each day after the air and vapor barrier has been installed. This method will increase the speed of application and reduce the number of nozzles required.

VapAir Seal Flashing Foam also offers the following features and benefits:

- Meets ASTM E283 air barrier standards
- Dries tack free within 30-60 seconds
- Can be trimmed within 2-5 minutes
- Fully cures within 1 hour
- Adheres to PVC pipe, wood, brick, block, and steel
- Compatible with VapAir Seal MD, VapAir Seal 725TR, and all of Carlisle's SureMB products
- Cured foam is resistant to extreme heat and cold (-200°F to 240°F)

Product Code	Weight/Carton	Stocking Location	Coverage Rate
326390	41 lbs	Carlisle, PA	205 board ft/carton

If you have any questions, or for more information, please contact your local manufacturer's representative.

Sincerely,



Paul A. Markel
Product Manager, Specialty Applications