CARLISLE'S AUTHORIZED APPLICATORS MARKETING ANNOUNCEMENT

FB-2013-13 Retrofitting Aged Single-Ply July 19, 2013

To: Carlisle SynTec Systems' Authorized Applicators

For many years, the Carlisle FleeceBACK® adhered roofing system has been used successfully to retrofit existing aged single-ply roofing systems such as EPDM, Hypalon, TPO, and PIB. A retrofit FleeceBACK adhered system provides a quick, non-intrusive and economical recover option for owners seeking a new 15- or 20-year warranty.

This aged single-ply retrofitting option incorporates a FleeceBACK membrane adhered to an acceptable, aged single-ply roof membrane using FAST[™] Adhesive applied in bead extrusions or full spray. Adjoining sheets of FleeceBACK EPDM membrane are then spliced together using 3"- or 6"-wide factory-applied SecurTAPE[™]. Sheets of FleeceBACK TPO and PVC membranes are joined together with a minimum 1-1/2"-wide hot-air weld.

The attached guide-spec contains information regarding products, warranty options, and installation. For more specific installation instructions, specifiers and applicators must refer to the applicable sections of Carlisle's technical manual.

Please contact Carlisle's Systems Design and Review department to discuss specific projects, as design considerations may vary based upon existing conditions, type of construction and location. If you would like installation advice for your first project, please contact your local Field Service Representative or one of the following FleeceBACK Technical Specialists.

Eastern U.S. - Kris Costas (717-609-9440) Kristopher.Costas@syntec.carlisle.com Central U.S. - Ben Brader (717-254-9298) Ben.Brader@syntec.carlisle.com Western U.S. - Dre Didriksen (541-653-7815) Dre.Didriksen@syntec.carlisle.com

Sincerely,

Scott J. Long Product Manager – FleeceBACK Roofing Systems

