

FleeceBACK[®] RL[™]

RapidLock Membrane

FleeceBACK RL EPDM, TPO & PVC

Code Approval Guide

November 2025

Table of Contents

UL Approvals:

ANSI UL - Class A.....	2
ANSI UL - Class B & C.....	3

FM Approvals:

InsulBase, SecurShield and SecurShield HD RL- New Construction.....	4-5
Reference Notes.....	6



UL Approval - ANSI/UL 790 Spread of Flame Test (Class A)
FleeceBACK RL Roofing Systems

Membrane Type: Sure-Seal FleeceBACK RL - Minimum 115-mil thickness
Sure-Weld FleeceBACK RL - Minimum 115-mil thickness
Sure-Flex FleeceBACK RL - Minimum 115-mil thickness

System ID	Deck Type	Barrier	Insulation	Cover Board	Maximum Slope		
					Sure-Seal FleeceBACK RL	Sure-Weld FleeceBACK RL	Sure-Flex FleeceBACK RL
1	Non-Combustible	N/A	(Optional) Any UL Classified Insulation, except EPS and XPS, any combination, any thickness	½-inch SecurShield HD RL	1/2"	1/2"	1/2"
2	Non-Combustible	N/A	InsulBase RL, SecurShield RL any combination, any thickness. Optionally, any UL Classified Insulation, except EPS and XPS may be used below.	N/A	1/2"	1/2"	1/2"
3	Combustible (1)	Minimum ¼-inch DensDeck®, DensDeck® Prime, SECUROCK Glass-Mat or SECUROCK Gypsum Fiber Roof Board (2)	(Optional) Any UL Classified Insulation, any combination, any thickness	½-inch SecurShield HD RL	1/2"	1/2"	1/2"
4	Combustible (1)	Minimum ¼-inch DensDeck®, DensDeck® Prime, SECUROCK Glass-Mat or SECUROCK Gypsum Fiber Roof Board (2)	InsulBase RL, SecurShield RL any combination, any thickness	N/A	1/2"	1/2"	1/2"
5	Combustible (1)	N/A	(OPTIONAL) Any UL Classified Insulation, except EPS and XPS, any combination, any thickness (3)	½-inch SecurShield HD RL (3)	1/2"	1/2"	1/2"
6	Combustible (1)	1 layer of Carlisle FR Base Sheet	Minimum 1.4-inch layer of InsulBase. (2)	½-inch SecurShield HD RL (2)	1/2"	1/2"	1/2"
7	Combustible (1)	N/A	Minimum 4-inch layer of any UL Classified EPS (2)	½-inch SecurShield HD RL (2)	1/2"	1/2"	1/2"

Footnotes:

- Any roof covering system listed for use over a combustible roof deck can be installed over a non-combustible roof deck and achieve the same classification.
- All insulation joints must be staggered a minimum of 6 in. from the deck joints or from the insulation joints directly below.
- All insulation joints must be staggered a minimum of 12 in. from the deck joints or from the insulation joints directly below.

UL Approval - ANSI/UL 790 Spread of Flame Test (Class B)
FleeceBACK RL Roofing Systems

Membrane Type: Sure-Seal FleeceBACK RL - Minimum 115-mil thickness
Sure-Weld FleeceBACK RL - Minimum 115-mil thickness
Sure-Flex FleeceBACK RL - Minimum 115-mil thickness

System ID	Deck Type	Barrier	Insulation	Cover Board	Maximum Slope		
					Sure-Seal FleeceBACK RL	Sure-Weld FleeceBACK RL	Sure-Flex FleeceBACK RL
1	Combustible (1)	N/A	Minimum 1.4-inch InsulBase. (2)	½-inch SecurShield HD RL (2)	1/2"	1/2"	1/2"

Footnotes:

- Any roof covering system listed for use over a combustible roof deck can be installed over a non-combustible roof deck and achieve the same classification.
- All insulation joints must be staggered a minimum of 6 in. from the deck joints or from the insulation joints directly below.

UL Approval - ANSI/UL 790 Spread of Flame Test (Class C)
FleeceBACK RL Roofing Systems

Membrane Type: Sure-Seal FleeceBACK RL - Minimum 115-mil thickness
Sure-Weld FleeceBACK RL - Minimum 115-mil thickness
Sure-Flex FleeceBACK RL - Minimum 115-mil thickness

System ID	Deck Type	Barrier	Insulation	Cover Board	Maximum Slope		
					Sure-Seal FleeceBACK RL	Sure-Weld FleeceBACK RL	Sure-Flex FleeceBACK RL
1	Combustible (1)	N/A	(Optional) Any UL Classified Insulation, any combination, any thickness	½-inch SecurShield HD RL	Unlimited	Unlimited	Unlimited
2	Combustible (1)	N/A	InsulBase RL, SecurShield RL any combination, any thickness. Optionally, any UL Classified Insulation, except EPS and XPS may be used below.	N/A	Unlimited	Unlimited	Unlimited

Footnote:

- Any roof covering system listed for use over a combustible roof deck can be installed over a non-combustible roof deck and achieve the same classification.

Factory Mutual Approvals
FleeceBACK RL Roofing Systems

InsulBase RL, SecurShield RL & SecurShield HD RL Polyiso Ratings - New Construction

Membrane Type: Sure-Seal FleeceBACK RL - Minimum 115-mil thickness
Sure-Weld FleeceBACK RL - Minimum 115-mil thickness
Sure-Flex FleeceBACK RL - Minimum 115-mil thickness

Insulation Adhesive: Flexible FAST and Flexible FAST Dual Tank- Applied in ribbons, splatter and/or full spray as noted.

Base Insulation Layer	Base Layer Fastening	Top Insulation Layer	Top Layer Fastening	Rating	Sure-Seal FleeceBACK RL	Sure-Weld FleeceBACK RL	Sure-Flex FleeceBACK RL
					RoofNAV Number		
Steel Deck (Min. 22-Gauge) (Note 1)							
Min. 1-1/2" InsulBase	Loose-laid	Min 2" SecurShield HD Composite RL	6 (5.33 sq. ft) (Notes 2 & 3)	1-90	Pending	Pending	Pending
Min. 1-1/2" InsulBase	Loose-laid	Min 2" InsulBase RL or SecurShield RL	8 (4 sq. ft) (Notes 2 & 3)	1-90	430381-0-0	430340-0-0	510074-0-0
Min. 1-1/2" InsulBase	Loose-laid	1/2" SecurShield HD RL	16 (2 sq. ft) (Notes 2, 3 & 4)	1-90	430386-0-0	430385-0-0	510075-0-0
Min. 1-1/2" InsulBase	Loose-laid	Min 2" InsulBase RL, SecurShield RL or SecurShield HD Composite RL	20 (1.6 sq. ft) (Notes 2 & 3)	1-150	430630-0-0	430426-0-0	510076-0-0
Min. 1-1/2" InsulBase	32 (1 sq. ft) (Note 2)	1/2" SecurShield HD RL	Flexible FAST Dual Tank-ribbons 4" o.c.	1-165 (C DECK)	445230-0-0	445223-0-0	510080-0-0
Min. 1-1/2" InsulBase	32 (1 sq. ft) (Note 2)	1/2" SecurShield HD RL	Flexible FAST Dual Tank-ribbons 4" o.c.	1-225 (E DECK)	445231-0-0	445229-0-0	510081-0-0
Steel Deck (Min. 22-Gauge)/ VapAir Seal 725TR and Cav-Grip III or 702 Primer							
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	8 (4 sq. ft) (Note 2)	Min 2" InsulBase RL or SecurShield RL over Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-90	479012-0-0	479016-0-0	Pending
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	8 (4 sq. ft) (Note 2)	1/2" SecurShield HD RL over Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-90	479018-0-0	479021-0-0	Pending
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	20 (1.6 sq. ft) (Note 2)	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL over Min. 1-1/2" InsulBase	Flexible FAST - Rig Splatter	1-135	Pending	Pending	Pending
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	32 (1 sq. ft) (Note 2)	1/2" SecurShield HD RL over Min 1.5" InsulBase or SecurShield	Flexible FAST - Rig Splatter.	1-225	Pending	Pending	Pending
Steel Deck (Min. 22-Gauge) / SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	8 (4 sq. ft) (Note 2)	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL over Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-90	Pending	Pending	Pending
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	20 (1.6 sq. ft) (Note 2)	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL over Min. 1-1/2" InsulBase	Flexible FAST - Rig Splatter.	1-135	Pending	Pending	Pending
Steel Deck (Min. 22-Gauge) / SureMB 90TG or 120TG Base Torch Applied							
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	8 (4 sq. ft) (Note 2)	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL over Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-90	Pending	Pending	Pending
Min. 1/2" Dens-Deck Prime or SECUROCK Gypsum Fiber	20 (1.6 sq. ft) (Note 2)	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL over Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 6" o.c.	1-135	Pending	Pending	Pending

Factory Mutual Approvals
FleeceBACK RL Roofing Systems

InsulBase RL, SecurShield RL & SecurShield HD RL Polyiso Ratings - New Construction

Membrane Type: Sure-Seal FleeceBACK RL - Minimum 115-mil thickness
Sure-Weld FleeceBACK RL - Minimum 115-mil thickness
Sure-Flex FleeceBACK RL - Minimum 115-mil thickness

Insulation Adhesive: Flexible FAST and Flexible FAST Dual Tank- Applied in ribbons, splatter and/or full spray as noted.

Base Insulation Layer	Base Layer Fastening	Top Insulation Layer	Top Layer Fastening	Rating	Sure-Seal FleeceBACK RL	Sure-Weld FleeceBACK RL	Sure-Flex FleeceBACK RL
					RoofNAV Number		
Structural Concrete Deck							
Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-285	460108-0-0	460110-0-0	Pending
Min. 1-1/2" InsulBase	Flexible FAST- Full Spray or Splatter	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL	Flexible FAST- Full Spray or Splatter	1-285	430413-0-0	430423-0-0	510077-0-0
Min. 1-1/2" InsulBase (Optional)	Flexible FAST- Full Spray or Splatter	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL	Flexible FAST- Full Spray or Splatter	1-285	430424-0-0	430425-0-0	Pending
Min. 1-1/2" InsulBase	Loose-laid	Min 2" InsulBase RL or SecurShield RL	20 (1.6 sq. ft) (Note 5)	1-150	Pending	460469-0-0	Pending
Structural Concrete Deck / VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer							
Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-285	460107-0-0	460109-0-0	Pending
Structural Concrete Deck / SureMB 70 SA and Cav-Grip III Primer							
Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-285	Pending	Pending	Pending
Structural Concrete Deck / SureMB 90TG and 120TG Base Torch Applied / Cut-Back Asphalt Primer							
Min. 1-1/2" InsulBase	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	Min 2" InsulBase RL, SecurShield RL or 1/2" SecurShield HD RL	Flexible FAST or Flexible FAST Dual Tank- ribbons 12" o.c.	1-285	Pending	Pending	Pending

Notes:

1. Optional VapAir Seal MD or the combination of gypsum and VapAir 725TR may be applied over the steel deck.
2. Securement using InsulFast Fastener & Insulation Fastening Plate.
3. Securement using InsulFast Fastener & SecurFast Plate.
4. Securement using HP Fastener & Insulation Fastening Plate.
5. Securement using CD-10 or HD 14-10 Fasteners & Insulation Fastening Plate.

Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC P.O. Box 7000, Carlisle, PA 17013
(800)-4SYNTEC (800-479-6832)

Carlisle, Sure-Seal, Sure-Weld & Sure-Flex FleeceBACK RL are Trademarks
of Carlisle SynTec Systems, a division of Carlisle Construction Materials, LLC

The contents of this issue represent the applicable information available at the time of publication. The contents of older issues are no longer accurate due to subsequent changes.