

Carlisle VSH Compliant Roofing Systems

Code Approval Guide

November 2025

Table of Contents

FM Approvals

SecurShield HD Composite New Construction.....	2-3
SecurShield HD Composite Recover.....	4
SecurShield HD Composite RL New Construction.....	5-6
SecurShield HD Composite RL Recover.....	7
EcoStorm VSH New Construction.....	8-10
EcoStorm VSH Recover.....	11
StormBase New Construction.....	12-13
StormBase Recover.....	14
Dens-Deck StormX New Construction.....	15-17
Dens-Deck StormX Recover.....	18
DEXcell FA VSH Glass Mat New Construction.....	19-20
DEXcell FA VSH Glass Mat Recover.....	21
SECUROCK Weather Defense Roof Board New Construction.....	22
Reference Notes.....	23



Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

SecurShield HD Composite Ratings - New Construction

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld EXTRA - .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. or Splatter for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-Seal FleeceBACK 145	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA
RoofNAV Number									
Steel Deck (Min. 22-Gauge)									
2" SecurShield HD Composite	8 (4 sq. ft.)	-	-	1-90	551139-0-0 (4" o.c.)	551132-0-0 (4" o.c.)	-	NA	NA
2" SecurShield HD Composite	20 (1.6 sq. ft.)	-	-	1-165	551283-0-0 (4" o.c.)	-	-	NA	NA
Min. 1-1/2" InsulBase Polyiso	Loose-Laid	2" SecurShield HD Composite	20 (1.6 sq. ft.)	1-165	-	551281-0-0 (4" o.c.)	-	NA	NA
2" SecurShield HD Composite	32 (1 sq. ft.)	-	-	1-270	551286-0-0 (4" o.c.)	551282-0-0 (4" o.c.)	-	NA	NA
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	551342-0-0	-	-	550948-0-0	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	551358-0-0	551344-0-0	573299-0-0	550949-0-0	550889-0-0
Min. 1-1/2" InsulBase Polyiso	16 (2 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-105	-	-	-	550957-0-0	550874-0-0
Min. 2" InsulBase Polyiso	20 (1.6 sq. ft.)	2" SecurShield HD Composite	4" ribbons of FAST	1-165	551364-0-0	551350-0-0	-	550930-0-0	-
Min. 2" InsulBase Polyiso	32 (1 sq. ft.)	2" SecurShield HD Composite	4" ribbons of FAST	1-225	-	-	-	550932-0-0	550876-0-0 (1-270)
Min. 1/2" DensDeck Prime or 5/8" Securock	16 (2 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	551346-0-0	-	-	-	550829-0-0
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer									
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	551362-0-0	-	551556-0-0	550956-0-0	-
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	551361-0-0	-	551554-0-0	550955-0-0	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-135	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer									
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-135	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied									
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-135	-	-	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

SecurShield HD Composite Ratings - New Construction

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld EXTRA - .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. or Splatter for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-Seal FleeceBACK 145	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA
					RoofNAV Number				
Concrete Deck									
Min. 1" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-180	-	-	-	-	-
2" SecurShield HD Composite	12" ribbons of FAST	-	-	1-180	551335-0-0	-	-	-	-
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-	-	-
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer									
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	556939-0-0	-	573298-0-0 (1-315)	-	534253-0-0 (1-315)
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-255	-	-	-	-	-
Concrete Deck with SureMB 70 SA with Cav-Grip III Primer									
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-	-	-
Concrete Deck with SureMB 90TG, 120TG Base Torch Applied and Cut-Back Asphalt Primer									
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-	-	550891-0-0
Gypsum Deck Tear-Off									
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-	-
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer									
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-	-
Lightweight Insulating Concrete over Steel Decking									
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-	552896-0-194470
Lightweight Insulating Concrete over Structural Concrete									
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

SecurShield HD Composite Ratings - Recover

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
 Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
 Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
 Sure-Weld EXTRA - .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. or Splatter for membrane attachment with FleeceBACK membranes
 Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA
					RoofNAV Numbers			
Concrete Deck								
-	-	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-	-
-	-	2" SecurShield HD Composite	6" ribbons of FAST	1-150	-	-	-	-
Gypsum Deck								
-	-	2" SecurShield HD Composite	6" ribbons of FAST	1-90	-	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing smooth Asphalt BUR, Modified Bitumen or single-ply system was FM approved at the time of installation. Direct membrane application over existing EPDM single-ply only.

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

SecurShield HD Composite RL Ratings - New Construction

Membrane Type:

Sure-Seal FleeceBACK RL - 115 or 145 membrane (black EPDM)
Sure-Weld FleeceBACK RL- 115 or 135 membrane (TPO)

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK RL	Sure-Seal FleeceBACK 145 RL	Sure-Weld FleeceBACK RL
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	2" SecurShield HD Composite RL	12" ribbons of FAST	1-90	-	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	2" SecurShield HD Composite RL	12" ribbons of FAST	1-90	-	-	-
Min. 1-1/2" InsulBase Polyiso	16 (2 sq. ft.)	2" SecurShield HD Composite RL	6" ribbons of FAST	1-105	-	-	-
Min. 2" InsulBase Polyiso	20 (1.6 sq. ft.)	2" SecurShield HD Composite RL	4" ribbons of FAST	1-165	-	-	-
Min. 2" InsulBase Polyiso	32 (1 sq. ft.)	2" SecurShield HD Composite RL	4" ribbons of FAST	1-225	-	-	-
Min. 1/2" DensDeck Prime or 5/8" Securock	16 (2 sq. ft.)	2" SecurShield HD Composite RL	12" ribbons of FAST	1-90	-	-	-
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite over Min.1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-135	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-135	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	2" SecurShield HD Composite	6" ribbons of FAST	1-135	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

SecurShield HD Composite RL Ratings - New Construction

Membrane Type:

Sure-Seal FleeceBACK RL - 115 or 145 membrane (black EPDM)
Sure-Weld FleeceBACK RL- 115 or 135 membrane (TPO)

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK RL	Sure-Seal FleeceBACK 145 RL	Sure-Weld FleeceBACK RL
					RoofNAV Number		
Concrete Deck							
Min. 1" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-180	-	-	-
2" SecurShield HD Composite	12" ribbons of FAST	-	-	1-180	-	-	-
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-255	-	-	-
Concrete Deck with SureMB 70 SA with Cav-Grip III Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-
Concrete Deck with SureMB 90TG, 120TG Base Torch Applied and Cut-Back Asphalt Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-225	-	-	-
Gypsum Deck Tear-Off							
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer							
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-
Lightweight Insulating Concrete over Steel Decking							
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-
Lightweight Insulating Concrete over Structural Concrete							
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	2" SecurShield HD Composite	12" ribbons of FAST	1-90	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

SecurShield HD Composite RL Ratings - Recover

Membrane Type: Sure-Seal FleeceBACK RL - 115 or 145 membrane (black EPDM)
Sure-Weld FleeceBACK RL - 115 or 135 membrane (TPO)

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-Weld FleeceBACK
					RoofNAV Numbers	
Concrete Deck						
-	-	2" SecurShield HD Composite RL	12" ribbons of FAST	1-90	-	-
-	-	2" SecurShield HD Composite RL	6" ribbons of FAST	1-150	-	-
Gypsum Deck						
-	-	2" SecurShield HD Composite RL	6" ribbons of FAST	1-90	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing smooth Asphalt BUR, Modified Bitumen or single-ply system was FM approved at the time of installation. Direct membrane application over existing EPDM single-ply only.

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

EcoStorm VSH Ratings - New Construction

Membrane Type:
Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP FleeceBack - 115 or 135 membrane (PVC)

Membrane Adhesive:
Flexible FAST and Flexible FAST Dual Tank heads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex FleeceBACK
Roof/NAV Number											
Steel Deck (Min. 22-Gauge)											
FM Approved	Loose laid	1/2" EcoStorm VSH	8 (4 sq. ft.)	1-90	461161-0-0	NA	461162-0-0	NA	NA	NA	NA
FM Approved	Loose laid	1/2" EcoStorm VSH	16 (2 sq. ft.)	1-90	461281-0-0	NA	461307-0-0	NA	NA	NA	NA
FM Approved	Loose laid	1/2" EcoStorm VSH	18 (1.8 sq. ft.)	1-120	461163-0-0	NA	461164-0-0	NA	NA	NA	NA
FM Approved	Loose laid	1/2" EcoStorm VSH	24 (1.33 sq. ft.)	1-165	461165-0-0	NA	461167-0-0	NA	NA	NA	NA
FM Approved	Loose laid	1/2" EcoStorm VSH	24 (1.33 sq. ft.)(19)	1-225	461166-0-0	NA	461168-0-0	NA	NA	NA	NA
FM Approved	Loose laid	1/2" EcoStorm VSH	32 (1 sq. ft.)(19)	1-270	461112-0-0	NA	461114-0-0	NA	NA	NA	NA
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	1/2" EcoStorm VSH	6" ribbons of FAST	1-90	461690-0-0	-	461360-0-0	554489-0-0	461118-0-0	560477-0-0	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	1/2" EcoStorm VSH over Min. 1" InsulBase	4" ribbons of FAST for EcoStorm VSH attachment and 12" o.c. for Polyiso	1-90	-	-	-	554492-0-0	-	560478-0-0	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	1/2" EcoStorm VSH	6" ribbons of FAST	1-90	461287-0-0	551572-0-0	461310-0-0	554546-0-0	461123-0-0	560581-0-0	-
Min. 1-1/2" InsulBase Polyiso	18 (1.8 sq. ft.)	1/2" EcoStorm VSH	6" ribbons of FAST	1-105	461171-0-0	-	461172-0-0	554482-0-0	461115-0-0	-	-
Min. 1-1/2" InsulBase Polyiso	24 (1.33 sq. ft.)	1/2" EcoStorm VSH	4" ribbons of FAST	1-150	-	-	-	554484-0-0	461117-0-0	-	-
Min. 2" InsulBase Polyiso	24 (1.33 sq. ft.)	1/2" EcoStorm VSH	4" ribbons of FAST	1-165	461206-0-0	-	461207-0-0	554483-0-0	461116-0-0	-	567713-0-0
Min. 1/2" DensDeck Prime or Securock	16 (2 sq. ft.)	1/2" EcoStorm VSH	6" ribbons of FAST	1-90	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer											
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	4" ribbons of FAST for EcoStorm VSH attachment and 12" o.c. for Polyiso	1-90	461290-0-0	551581-0-0	461314-0-0	554517-0-0	461154-0-0	560465-0-0	-
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/2" EcoStorm VSH over 1" Insulfoam Roofing EPS	4" ribbons of FAST for EcoStorm VSH attachment and 6" o.c. for EPS	1-90	-	-	-	554488-0-0	461121-0-0	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	FAST Rig Splatter	1-135	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	32 (1 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	FAST Rig Splatter	1-240	-	-	-	-	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

EcoStorm VSH Ratings - New Construction

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP FleeceBack - 115 or 135 membrane (PVC)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex FleeceBACK
					RoofNAV Number						
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer											
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-90	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied											
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-90	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/2" EcoStorm VSH over 1-1/2" InsulBase Polyiso	6" ribbons of FAST	1-135	-	-	-	-	-	-	-
Concrete Deck											
Min. 1" InsulBase Polyiso	12" ribbons of FAST	1/2" EcoStorm VSH	12" ribbons of FAST	1-225	461264-0-0 (1-270)	551576-0-0	461295-0-0 (1-315)	554547-0-0	461120-0-0	560480-0-0	-
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	1/2" EcoStorm VSH	12" ribbons of FAST	1-225	461266-0-0 (1-180)	-	-	554497-0-0	461130-0-0	-	-
Min. 2" Insulfoam Channel Dry EPS	12" ribbons of FAST	1/2" EcoStorm VSH over Min. 2" Insulfoam Roofing EPS	4" ribbons of FAST for EcoStorm VSH attachment and 12" o.c. for EPS	1-285	-	551575-0-0 (1-180)	-	554521-0-0	-	-	-
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	1/2" EcoStorm VSH	12" ribbons of FAST	1-705	-	-	461192-0-0	-	-	-	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	1/2" EcoStorm VSH	6" ribbons of FAST	1-90	-	-	-	554493-0-0	461125-0-0	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft)	1/2" EcoStorm VSH	6" ribbons of FAST	1-90	-	-	-	554496-0-0	461126-0-0	-	-
Min. 3/4" Optim-R	6" ribbons of FAST	1/2" EcoStorm VSH	6" ribbons of FAST	1-120	461294-0-0	551571-0-0 (1-90)	-	554519-0-0	461159-0-0	-	-
1/2" EcoStorm VSH	FAST Rig Splatter	-	-	1-270	-	551577-0-0	-	-	-	-	-
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer											
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	EcoStorm VSH	12" ribbons of FAST	1-225 (Cav-Grip III)	461267-0-0	551564-0-0	461298-0-0	-	461137-0-0	560463-0-0	567708-0-0
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	EcoStorm VSH	12" ribbons of FAST	1-255 (Cav-Grip III)	-	-	-	-	461131-0-0	-	-
Min. 3/4" Optim-R	6" ribbons of FAST	EcoStorm VSH	6" ribbons of FAST	1-165	461292-0-0	551570-0-0 (1-90)	-	554518-0-0	461157-0-0	-	-
Min. 3/4" Optim-R	12" ribbons of FAST	EcoStorm VSH	12" ribbons of FAST	1-60	-	551569-0-0	-	-	461155-0-0	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

EcoStorm VSH Ratings - New Construction

Membrane Type:
Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP FleeceBack - 115 or 135 membrane (PVC)

Membrane Adhesive:
Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex FleeceBACK
RoofNAV Number											
Concrete Deck with SureMB 70 SA with Cav-Grip III Primer											
Min. 1/2" InsulBase Polyiso	Full-Coverage FAST	EcoStorm VSH	12" ribbons of FAST	1-285	519866-0-0	-	519865-0-0	-	-	560576-0-0	-
Concrete Deck with SureMB 90TG, 1201G Base Torch Applied and Cut-Back Asphalt Primer											
Min. 1/2" InsulBase Polyiso	Full-Coverage FAST	EcoStorm VSH	12" ribbons of FAST	1-225	461272-0-0 (1-255)	551568-0-0 (1-255)	-	554514-0-0	461143-0-0	560470-0-0	567709-0-0
Gypsum Deck Tear-Off											
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	EcoStorm VSH	6" ribbons of FAST	1-90	-	-	524130-0-0	-	486677-0-0	-	-
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer											
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	EcoStorm VSH	6" ribbons of FAST	1-90	-	-	-	-	486676-0-0	-	-
(Celcore) Cellular Lightweight Insulating Concrete Over Steel Decking (Min. 22 Gauge)											
FM Approved	Loose laid	EcoStorm VSH	12 (2.67 sq. ft)	1-75	-	-	-	NA	NA	-	-
FM Approved	Loose laid	EcoStorm VSH	16 (2 sq. ft)	1-90	-	-	-	NA	NA	-	-
-	-	EcoStorm VSH	12 (2.67 sq. ft)	1-75	-	-	-	NA	NA	-	-
-	-	EcoStorm VSH	16 (2 sq. ft)	1-90	-	-	-	NA	NA	-	-
(Celcore) Cellular Lightweight Insulating Concrete Over Structural Concrete Decking											
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	EcoStorm VSH	4" ribbons of FAST	1-135	-	-	-	-	461134-0-50916	560578-0-50916	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

EcoStorm VSH Ratings - Recover

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld EXTRA - .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA	Sure-Flex PVC
					RoofNAV Number				
Steel Deck (Min. 22-Gauge)									
-	-	EcoStorm VSH	12 (2.67 sq. ft)	1-75	-	-	-	NA	NA
-	-	EcoStorm VSH	16 (2 sq. ft)	1-90	461810-0-0	-	461519-0-0	NA	NA
-	-	EcoStorm VSH	32 (1 sq. ft.)	1-270			524216-0-0	-	-
Max. 1" InsulBase	Loose-laid	EcoStorm VSH	8 (4 sq. ft)	1-90	-	-	552118-0-0	NA	NA
-	-	EcoStorm VSH	6" ribbons of FAST	1-150	-	-	-	489958-0-0	-
Concrete Deck									
Min. 1/2" InsulBase Polyiso or SecurShield	6" ribbons of FAST	EcoStorm VSH	12" ribbons of FAST	1-90	461280-0-0	-	467534-0-0	-	-
-	-	EcoStorm VSH	6" ribbons of FAST	1-150	466720-0-0	-	466721-0-0	-	-
Gypsum Deck									
-	-	EcoStorm VSH	6" ribbons of FAST	1-90	-	-	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing smooth Asphalt BUR, Modified Bitumen or single-ply system was FM approved at the time of installation. Direct membrane application over existing EPDM single-ply only.

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

StormBase Ratings - New Construction

Membrane Type: Sure-White FleeceBACK - 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld EXTRA - .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA
Steel Deck (Min. 22 Gauge)							
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 2" StormBase	17 (1.9 sq. ft)	1-150	439043-0-0	439042-0-0	NA
Min. 1-1/2" InsulBase Polyiso	Loose laid	Min. 2" StormBase	32 (1 sq. ft)(19)	1-270	439045-0-0	439044-0-0	NA
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	Min. 2" StormBase	12" ribbons of FAST	1-90	439066-0-0	439065-0-0	-
Min. 1/2" Dens Deck Prime or Securock	16 (2 sq. ft.)	Min. 2" StormBase over min 1-1/2" InsulBase	12" ribbons of FAST	1-90	439068-0-0	439067-0-0	-
Min. 1/2" Dens Deck Prime or Securock	16 (2 sq. ft.)	Min. 1-1/2" Insulam OSB over Insulfoam EPS	6" ribbons of FAST	1-90	439058-0-0	-	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft)	Min. 2" StormBase	12" ribbons of FAST	1-90	439064-0-0	439063-0-0	427172-0-0
Min. 2" InsulBase Polyiso	8 (4 sq. ft)	Min. 2" StormBase	12" ribbons of FAST	1-90	-	-	427201-0-0
Min. 1-1/2" Polyiso	Loose laid	Min. 2" StormBase	Full-Coverage FAST	1-90	-	-	419427-0-0
Min. 1/2" DensDeck Prime or 5/8" Securock	16 (2 sq. ft)	Min. 2" StormBase	12" ribbons of FAST	1-90	-	-	427202-0-0
Min. 3" Insulfoam VIII over 1/2" Dens Deck	16 (2 sq. ft)	Min. 1-1/2" Insulam OSB	6" ribbons of FAST	1-150	-	-	434590-0-0
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer							
Min. 1/2" Dens Deck Prime or Securock	16 (2 sq. ft.)	Min. 2" StormBase over min 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	439059-0-0	-
Min. 1/2" Dens Deck Prime or Securock	16 (2 sq. ft.)	Min. 2" StormBase	12" ribbons of FAST	1-90	439062-0-0	439061-0-0	434469-0-0
Min. 1/2" Dens Deck Prime or Securock	20 (1.6 sq. ft.)	Min. 2" StormBase	6" ribbons of FAST	1-135	Pending	Pending	Pending
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" Dens Deck Prime or Securock	16 (2 sq. ft.)	Min. 2" StormBase	12" ribbons of FAST	1-90	Pending	Pending	Pending
Min. 1/2" Dens Deck Prime or Securock	20 (1.6 sq. ft.)	Min. 2" StormBase	6" ribbons of FAST	1-135	Pending	Pending	Pending
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied							
Min. 1/2" Dens Deck Prime or Securock	16 (2 sq. ft.)	Min. 2" StormBase over min 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-
Min. 1/2" Dens Deck Prime or Securock	20 (1.6 sq. ft.)	Min. 2" StormBase	6" ribbons of FAST	1-135	Pending	Pending	Pending

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

StormBase Ratings - New Construction

Membrane Type: Sure-White FleeceBACK - 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld EXTRA - .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA
Concrete Deck							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-315	-	-	427190-0-0
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	Full-Coverage FAST	1-270	439021-0-0	439020-0-0	-
-	-	Min. 2" StormBase	Full-Coverage FAST	1-270	439019-0-0	439018-0-0	-
-	-	Min. 2" StormBase	12" ribbons of FAST	1-165	-	-	434470-0-0
-	-	Min. 2" StormBase	Hot Asphalt	1-300	-	-	419424-0-0
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-255	439023-0-0	439022-0-0	427203-0-0
Concrete Deck with SureMB 70 SA and Cav-Grip III Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-270	Pending	Pending	Pending
Concrete Deck with SureMB 90TG and 120TG Base Torch Applied/Cut-Back Asphalt Primer							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-270	-	444182-0-0	-
Gypsum Deck Tear-Off							
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-90	-	-	-
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer							
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-90	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

StormBase Ratings - Recover

Membrane Type: Sure-White FleeceBACK - 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld EXTRA - .080" (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld EXTRA membrane

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld EXTRA
Concrete Deck							
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	Min. 2" StormBase	12" ribbons of FAST	1-90	-	-	-
-	-	Min. 2" StormBase	Full-Coverage FAST	1-90	-	-	419421-0-0

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing smooth Asphalt BUR, Modified Bitumen or single-ply system was FM approved at the time of installation. Direct membrane application over existing EPDM single-ply only.

DensDeck StormX Prime Ratings - New Construction

Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex KEE HP - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP Fleeceback - 115 or 135 membrane (PVC)

Membrane Type:
Flexible FAST and Flexible FAST Dual Task bonds 4" o.c. or Splitter for membrane attachment with FleeceBACK membranes
Membrane Adhesive:
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes
Hydrobond Water Based PVC bonding adhesive for Sure-Flex PVC, Sure-Flex Fleeceback and Sure-Flex KEE HP Fleeceback (HYB)
Cav-Grip PVC Adhesive for Sure-Flex PVC (CG)
Low VOC PVC Bonding Adhesive for Sure-Flex PVC and Sure-Flex KEE HP membranes (LV)

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (see details 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (see details 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex KEE HP (LVOC only)	Sure-Flex FleeceBack	Sure-Flex KEE HP FleeceBack
					RoofNAV Number								
					Steel Deck (Min. 22-Gauge)								
Min. 1-1/2" InsulBase Polyiso	Loose-Laid	5/8" DensDeck StormX	8 (4 sq. ft.)	1-90	567015-0-0	-	577373-0-0	NA	NA	NA	NA	NA	NA
Min. 1-1/2" InsulBase Polyiso	Loose-Laid	5/8" DensDeck StormX	18 (1.8 sq. ft.)	1-135	567011-0-0	-	567004-0-0	NA	NA	NA	NA	NA	NA
Min. 1-1/2" InsulBase Polyiso	Loose-Laid	5/8" DensDeck StormX	32 (1 sq. ft.)	1-165	-	-	567010-0-0	NA	NA	NA	NA	NA	NA
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	5/8" DensDeck StormX	12" ribbons of FAST	1-90	557285-0-0	551675-0-0	551609-0-0	-	-	560705-0-0 (HYB) 559522-0-0 (CG)	557691-0-0	554266-0-0	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	5/8" DensDeck StormX over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	557284-0-0	551674-0-0	551601-0-0	478034-0-0	478034-0-0	561192-0-0 (HYB) 559523-0-0 (CG)	-	554295-0-0	568415-0-0
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	5/8" DensDeck StormX	12" ribbons of FAST	1-90	557287-0-0	551679-0-0	-	481545-0-0	477811-0-0	554346-0-0 (HYB) 559175-0-0 (CGLV)	-	554273-0-0	568407-0-0
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	5/8" DensDeck StormX over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	557286-0-0	551678-0-0	551612-0-0	-	-	561193-0-0 (HYB) 559173-0-0 (CGLV)	-	554296-0-0	568420-0-0
Min. 2" InsulBase Polyiso	16 (2 sq. ft.)	5/8" DensDeck StormX	12" ribbons of FAST	1-120	557282-0-0	551699-0-0	551654-0-0	478621-0-0	478621-0-0	560133-0-0 (LV) 559532-0-0 (CG)	557692-0-0	-	-
Min. 2" InsulBase Polyiso	16 (2 sq. ft.)	5/8" DensDeck StormX over Min. 1" InsulBase	12" ribbons of FAST	1-105	557283-0-0	-	-	-	-	559535-0-0 (CG)	-	-	-
Min. 2" InsulBase Polyiso	20 (1.6 sq. ft.)	5/8" DensDeck StormX	6" ribbons of FAST	1-135	557281-0-0	551702-0-0	551656-0-0	478620-0-0	478620-0-0	561194-0-0 (HYB) (1-120) 559531-0-0 (CG)	-	-	-
Min. 2" InsulBase Polyiso	32 (1 sq. ft.)	5/8" DensDeck StormX	4" ribbons of FAST	1-165 C-Deck	-	-	-	478622-0-0	478624-0-0	560118-0-0 (LV) 559533-0-0 (CG)	-	-	-
Min. 2" InsulBase Polyiso	32 (1 sq. ft.)	5/8" DensDeck StormX	4" ribbons of FAST	1-225 E-Deck	-	-	551652-0-0	478623-0-0	478625-0-0	-	-	-	568440-0-0
Min. 1/2" DensDeck Prime	16 (2 sq. ft.)	5/8" DensDeck StormX and Min. 1.5" InsulBase	12" ribbons of FAST	1-90	-	-	551653-0-0	477985-0-0	477983-0-0	-	-	564992-0-0	568429-0-0
Min. 1/2" DensDeck Prime	16 (2 sq. ft.)	5/8" DensDeck StormX and Min. 1" InsulBase Roofing EPS in adhesive	6" ribbons of FAST	1-90	-	-	-	-	-	560129-0-0 (LV)	-	-	-

DensDeck StormX Prime Ratings - New Construction

Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex KEE HP - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP Fleeceback - 115 or 135 membrane (PVC)

Flexible FAST and Flexible FAST Dual Task bonds 4" o.c. or Sphaler for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes
Hydrobond Water Based PVC bonding adhesive for Sure-Flex PVC, Sure-Flex Fleeceback and Sure-Flex KEE HP Fleeceback (HYB)
Cav-Grip PVC Adhesive for Sure-Flex PVC (CG)
Low VOC PVC Bonding Adhesive for Sure-Flex PVC and Sure-Flex KEE HP membranes (LV)

Roof Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex KEE HP (LVOC only)	Sure-Flex FleeceBack	Sure-Flex KEE HP FleeceBack
					Roof/NAV Number								
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer													
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DensDeck StormX over 1-1/2" InsullBase Polyiso	12" rbboms of FAST	1-90	557289-0-0	551692-0-0	551624-0-0	478004-0-0	478004-0-0	561196-0-0 (HYB) 559521-0-0 (CG)	-	581146-0-0	-
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DensDeck StormX over 1" Insullium Roofing EPS	6" rbboms of FAST	1-90	-	-	-	-	-	560128-0-0 (LV)	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	5/8" DensDeck StormX over 1-1/2" InsullBase Polyiso	FAST - Rig Splatter	1-135	-	-	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer													
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DensDeck StormX over 1-1/2" InsullBase Polyiso	12" rbboms of FAST	1-90	-	-	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	5/8" DensDeck StormX over 1-1/2" InsullBase Polyiso	6" rbboms of FAST	1-135	-	-	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied													
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DensDeck StormX over 1-1/2" InsullBase Polyiso	12" rbboms of FAST	1-90	-	-	-	478647-0-0	478648-0-0	559489-0-0 (CGLV)	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	5/8" DensDeck StormX over 1-1/2" InsullBase Polyiso	6" rbboms of FAST	1-135	-	-	-	-	-	-	-	-	-
Concrete Deck													
Min. 1.5" InsullBase Polyiso	12" rbboms of FAST	5/8" DensDeck StormX	12" rbboms of FAST	1-465	-	551608-0-0 (1-270)	551638-0-0 (1-315)	477785-0-0	477786-0-0	559178-0-0 (CGLV)	-	554276-0-0 (1-315)	554304-0-0 (1-315)
Min. 2" Insullium Roofing EPS	12" rbboms of FAST	5/8" DensDeck StormX	12" rbboms of FAST	1-465	-	-	-	478649-0-0	478650-0-0	-	-	-	-

DensDeck StormX Prime Ratings - New Construction

Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex KEE HP - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP Fleeceback - 115 or 135 membrane (PVC)

Flexible FAST and Flexible FAST Dual Task beads 4" o.c. or Splitter for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes
Hydrobond Water Based PVC bonding adhesive for Sure-Flex PVC, Sure-Flex Fleeceback and Sure-Flex KEE HP Fleeceback (HYB)
Cav-Grip PVC Adhesive for Sure-Flex PVC (CG)
Low VOC PVC Bonding Adhesive for Sure-Flex PVC and Sure-Flex KEE HP membranes (LV)

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (see details for fasteners per notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (see details for fasteners per notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex KEE HP (LVOC only)	Sure-Flex FleeceBack	Sure-Flex KEE HP FleeceBack
					Roof/NAV Number								
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer													
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-255	-	551693-0-0	551635-0-0	478007-0-0	478007-0-0	561198-0-0 (HYB) 559179-0-0 (CGLV)	-	554264-0-0	554300-0-0
Min. 1" Insulfoam Roofing EPS	12" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-315	-	-	-	-	-	559493-0-0 (CGLV)	-	-	568433-0-0 (1-90)
Concrete Deck with SureMB 70 SA and Cav-Grip III Primer													
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-255	-	-	-	557083-0-0	557083-0-0	554437-0-0 (HYB) 559530-0-0 (CGLV)	-	-	-
Concrete Deck with SureMB 90TG, 120TG Base Torch Applied and Cut-Back Asphalt Primer													
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-315	-	551696-0-0 (1-255)	551646-0-0 (1-255)	478014-00	478014-0-0	561203-0-0 (HYB)	-	554269-0-0	568435-0-0 (1-255)
Min. 1" Insulfoam Roofing EPS	12" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	568437-0-0
Gypsum Deck Tear-Off													
Min. 1-1/2" InsulBase Polyiso	FAST Splitter	5/8" DensDeck StormX	FAST Splitter	1-90	-	-	551594-0-0	479141-0-0	479141-0-0	559538-0-0 (CGLV)	-	564976-0-0	568387-0-0
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer													
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-90	-	-	-	478628-0-0	478628-0-0	-	-	-	-
Lightweight Insulating Concrete over Steel Decking													
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-135	-	551683-0-194470	551619-0-194470	497923-0-194470	497923-0-194470	-	-	-	568425-0-194470
Lightweight Insulating Concrete over Structural Concrete													
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-90	-	551684-0-50916	551622-0-50916	497941-0-50916	497941-0-50916	561197-0-50916 (HYB) 559491-0-50916 (CGLV)	-	564974-0-50916	568426-0-50916

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

DensDeck StormX Prime Ratings - Recover

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. or Splatter for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes
Hydrobond Water Based PVC bonding adhesive for Sure-Flex PVC, Sure-Flex Fleeceback and Sure-Flex KEE HP Fleeceback

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure- Weld EXTRA	Sure-Flex PVC	Sure-Flex Fleeceback {PVC and KEE HP}
					RoofNAV Number						
Steel Deck (Min. 22-Gauge)											
-	-	5/8" DensDeck StormX	8 (4 sq. ft.)	1-90	569727-0-0	-	577374-0-0	-	-	-	-
-	-	5/8" DensDeck StormX	18 (1.8 sq. ft.)	1-135	-	-	569728-0-0	-	-	-	-
-	-	5/8" DensDeck StormX	6" ribbons of FAST	1-90	-	-	-	497942-0-0	497942-0-0	560137-0-0	-
-	-	5/8" DensDeck StormX	6" ribbons of FAST	1-135	-	-	-	-	-	581760-0-0	581140-0-0
Max. 1" InsulBase Polyiso or SecurShield	16 (2 sq. ft.)	5/8" DensDeck StormX	12" ribbons of FAST	1-90	-	-	569729-0-0	-	-	560122-0-0	-
Concrete Deck											
Min. 1/2" InsulBase Polyiso or SecurShield	6" ribbons of FAST	5/8" DensDeck StormX	12" ribbons of FAST	1-90	-	-	-	-	-	-	-
-	-	5/8" DensDeck StormX	6" ribbons of FAST	1-150	-	-	-	-	-	-	-
Gypsum Deck											
-	-	5/8" DensDeck StormX	6" ribbons of FAST	1-90	-	-	-	-	-	-	-
Tectum Deck											
Min. 1" InsulBase Polyiso	20 (1.6 sq. ft.)	5/8" DensDeck StormX	12" ribbons of FAST	1-90	-	-	-	477989-0-0	477989-0-0	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing smooth Asphalt BUR, Modified Bitumen or single-ply system was FM approved at the time of installation. Direct membrane application over existing EPDM single-ply only.

DEXcell FA VSH Glass Mat Ratings - New Construction

Membrane Type:
Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
Sure-Flex - .060" & .080" membrane (PVC)
Sure-Flex KEE HP - .060" & .080" membrane (PVC)
Sure-Flex and Sure-Flex KEE HP FleeceBack - 115 or 135 membrane (PVC)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. or Splatter for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure-Weld EXTRA	Sure-Flex	Sure-Flex KEE HP (LVOC only)	Sure-Flex FleeceBack	Sure-Flex KEE HP FleeceBack
					RoofNAV Number								
Steel Deck (Min. 22-Gauge)													
Min. 1-1/2" InsulBase Polyiso	Loose-Laid	5/8" DEXcell FA VSH	10 (3.2 sq. ft.)	1-90	-	-	577375-0-0	NA	NA	NA	NA	NA	NA
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	5/8" DEXcell FA VSH	12" ribbons of FAST	1-90	-	-	581691-0-0	-	-	-	-	-	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	581675-0-0	-	-	-	-	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	5/8" DEXcell FA VSH	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	568397-0-0
Min. 2" InsulBase Polyiso	8 (4 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime	16 (2 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer													
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	FAST - Rig Splatter	1-135	-	-	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer													
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	6" ribbons of FAST	1-135	-	-	-	-	-	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied													
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	5/8" DEXcell FA VSH over Min. 1-1/2" InsulBase	6" ribbons of FAST	1-135	-	-	-	-	-	-	-	-	-

Concrete Deck													
Min. 1.5" InsulBase Polyiso	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-315	-	-	581703-0-0	-	-	-	-	-	-
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-465	-	-	-	-	-	-	-	-	-
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer													
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-255	-	-	-	-	-	-	-	-	-
Min. 1" Insulfoam Roofing EPS	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-315	-	-	-	-	-	-	-	-	-
Concrete Deck with SureMB 70 SA and Cav-Grip III Primer													
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-255	-	-	-	-	-	-	-	-	-
Concrete Deck with SureMB 90TG, 120TG Base Torch Applied and Cut-Back Asphalt Primer													
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-315	-	-	-	-	-	-	-	-	-
Gypsum Deck Tear-Off													
Min. 1-1/2" InsulBase Polyiso	FAST Splatter	5/8" DEXcell FA VSH	FAST Splatter	1-90	-	-	-	-	-	-	-	-	-
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer													
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-
Lightweight Insulating Concrete over Steel Decking													
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-135	-	-	-	-	-	-	-	-	-
Lightweight Insulating Concrete over Structural Concrete													
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-90	-	-	-	-	-	-	-	-	-

Factory Mutual Approvals
Carlisle VSH Compliant Roofing System

DEXcell FA VSH Glass Mat Ratings - Recover

Membrane Type: Sure-Seal FleeceBACK - 115 or 145 membrane (black EPDM)
Sure-White FleeceBACK - 115 or 145 membrane (white EPDM)
Sure-Weld FleeceBACK - 115 or 135 membrane (TPO)
Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)

Membrane Adhesive: Flexible FAST and Flexible FAST Dual Tank beads 4" o.c. or Splatter for membrane attachment with FleeceBACK membranes
Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes
Hydrobond Water Based PVC bonding adhesive for Sure-Flex PVC, Sure-Flex Fleeceback and Sure-Flex KEE HP Fleeceback

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FleeceBACK	Sure-White FleeceBACK	Sure-Weld FleeceBACK	Sure-Weld	Sure- Weld EXTRA	Sure-Flex PVC	Sure-Flex Fleeceback {PVC and KEE HP}
					RoofNAV Number						
Steel Deck (Min. 22-Gauge)											
-	-	5/8" DEXcell FA VSH	10 (3.2 sq. ft)	1-90	-	-	579498-0-0	NA	NA	NA	NA
-	-	5/8" DEXcell FA VSH	6" ribbons of FAST	1-90	-	-	-	-	-	-	-
Max. 1" InsulBase Polyiso or SecurShield	20 (1.6 sq. ft.)	5/8" DEXcell FA VSH	12" ribbons of FAST	1-90	-	-	-	-	-	-	-
Concrete Deck											
Min. 1/2" InsulBase Polyiso or SecurShield	6" ribbons of FAST	5/8" DEXcell FA VSH	12" ribbons of FAST	1-90	-	-	-	-	-	-	-
-	-	5/8" DEXcell FA VSH	6" ribbons of FAST	1-150	-	-	-	-	-	-	-
Gypsum Deck											
-	-	5/8" DEXcell FA VSH	6" ribbons of FAST	1-90	-	-	-	-	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing smooth Asphalt BUR, Modified Bitumen or single-ply system was FM approved at the time of installation. Direct membrane application over existing EPDM single-ply only.

Factory Mutual Approvals

SECUROCK Weather Defense Roof Board Ratings - New Construction

Membrane Type: Sure-Seal FR Non-Reinforced - .090" membrane (black EPDM)
 Sure-Weld and Sure-Weld EXTRA - .060" or .080" membrane (TPO)
 Sure-Flex KEE HP FleeceBack - 135 membrane (PVC)

Membrane Adhesive: 90-8-30A Bonding Adhesive for Sure-Seal FR Non-Reinforced
 Sure-Weld Bonding Adhesive, Low VOC Bonding Adhesive or Cav-Grip III Adhesive/Primer for Sure-Weld and Sure-Weld EXTRA membranes
 Hydrobond Water Based PVC bonding adhesive for Sure-Flex KEE HP Fleeceback (HYB)

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 11, 12 & 13)	Rating	Sure-Seal FR NR	Sure-Weld	Sure-Weld EXTRA	Sure-Flex KEE HP FleeceBack
					RoofNAV Number			
Steel Deck (Min. 22-Gauge)								
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	5/8" Weather Defense	12" ribbons of FAST	1-90	-	-	-	-
Min. 1-1/2" InsulBase Polyiso	10 (3.2 sq. ft.)	5/8" Weather Defense over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft)	5/8" Weather Defense	12" ribbons of FAST	1-90	581754-0-0	-	-	-
Min. 2" InsulBase Polyiso	8 (4 sq. ft)	5/8" Weather Defense over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	581699-0-0	-	-	-
Min. 1/2" DensDeck Prime	16 (2 sq. ft.)	5/8" Weather Defense over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip III or 702 Primer								
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" Weather Defense over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip III Primer								
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" Weather Defense over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	581757-0-0	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 90TG or 120TG Base Torch Applied								
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	5/8" Weather Defense over Min. 1-1/2" InsulBase	12" ribbons of FAST	1-90	-	-	-	-
Concrete Deck								
Min. 1.5" InsulBase Polyiso	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-315	-	-	-	554304-0-0
Min. 2" Insulfoam Roofing EPS	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-465	-	-	-	-
Concrete Deck with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer								
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-255	-	-	-	-
Min. 1" Insulfoam Roofing EPS	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-315	-	-	-	-
Concrete Deck with SureMB 70 SA and Cav-Grip III Primer								
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-255	-	-	-	-
Concrete Deck with SureMB 90TG, 120TG Base Torch Applied and Cut-Back Asphalt Primer								
Min. 1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-315	-	-	-	-
Gypsum Deck Tear-Off								
Min. 1-1/2" InsulBase Polyiso	FAST Splatter	5/8" Weather Defense	FAST Splatter	1-90	-	-	-	-
Gypsum Deck Tear-Off with VapAir Seal 725TR and Cav-Grip III, 702-LV or 702 Primer								
Min. 1-1/2" InsulBase Polyiso	12" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-90	-	-	-	-
Lightweight Insulating Concrete over Steel Decking								
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-135	-	-	-	-
Lightweight Insulating Concrete over Structural Concrete								
Min. 1-1/2" InsulBase Polyiso	4" ribbons of FAST	5/8" Weather Defense	12" ribbons of FAST	1-90	-	-	-	-

Carlisle VSH Compliant Roofing System

Reference Notes

1. DELETED

2. DELETED

3. DELETED

4. DELETED

5. DELETED

6. DELETED

7. DELETED

8. DELETED

9. DELETED

10. Existing adhered or mechanically fastened EPDM or Hypalon roofing systems. Contact Carlisle regarding suitability and specific requirements.

11. Sure-Seal HP fastener/Sure-Seal Insulation plate.

12. InsulFAST fastener/Sure-Seal Insulation plate.

13. InsulFAST fastener/SecurFAST Insulation Fastening plate.

14. Testing conducted on minimum 22 gauge FM approved Grade C Steel Deck fastened 4 feet on center.

15. UL 580 Test Standard – “Tests for Uplift Resistance of Roof Assemblies”. This test method subjects a 10’ x 10’ sample to various static and oscillating air pressures to determine uplift resistance.

16. ANSI/UL 1897 Test Standard – “Standard Test Method for Uplift Resistance for Roof Covering Systems”. This test method subjects a 10’ x 10’ sample to differential static uplift pressures to determine resistance. This test is essentially the same as Factory Mutual’s (FM) Uplift Testing only the table size is different.

17. Testing was conducted with EPDM FleeceBACK membrane; however, FM testing has shown that Sure-Weld FleeceBACK membrane secured with FAST Adhesive is equivalent.

18. 80 ksi with one fastener per attachment point.

19. 80 ksi with two fasteners per attachment point.

Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC, P.O. Box 7000, Carlisle, PA 17013
(800)-4SYNTEC (800-479-6832)

Carlisle, Sure-Seal, Sure-Flex, Sure-Weld, Sure-White, FleeceBACK and FAST are Trademarks
of Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC
DensDeck Prime is a Trademark of Georgia-Pacific

The contents of this issue represent the applicable information available at the time of publication. The contents of older issues are no longer accurate due to subsequent changes.

2025 Copyright Carlisle SynTec Systems, a division of Carlisle Construction Materials LLC