


# VERSIFLEECE TPO

## Mechanically Attached Roofing System



### Typical Application

- 1** VersiFleece® TPO Membrane
- 2** Versico Fasteners and Plates
- 3** Acceptable Insulation
- 4** Approved Roof Deck

<b>Colors</b>	White, Gray and Tan*
<b>Standard Thicknesses</b>	100, 115 and 135
<b>Standard Widths</b>	6' and 12'
<b>Standard Lengths</b>	50', 75' and 100'

\*Special Colors Available in 115-mil VersiFleece TPO Membranes

- Membranes resist hail damage and tolerate frequent foot traffic
- VersiWeld® membranes are considered environmentally friendly as they do not contain chlorine or plasticizers
- Industry-leading OctaGuard XT™ Weathering Package provides improved weatherability, durability and long-term rooftop performance

### System Features and Benefits

- UL Class A fire rating
- 12' sheet reduces seams by over 75% compare to Modified Bitumen sheets
- Exceptional puncture resistance
- Reflectivity warranty available
- Ideal for recovering smooth BUR, Modified Bitumen or Mineral Cap Sheet
- VersiFleece TPO's smooth top-ply surface resists dirt pickup and bacteria growth and provides for a clean monolithic seam weld

### Installation

VersiFleece TPO Mechanically Attached Roofing System utilizes 45-, 60- or 80-mil white, gray or tan VersiWeld thermoplastic polyolefin (TPO) membrane laminated to a non-woven polyester fleece backing.

Insulation is mechanically fastened to an acceptable roof deck. VersiFleece TPO membrane sheets are mechanically attached to the deck with Versico's HPVX or HPV-XL Fasteners and Plates. Adjoining sheets are overlapped and joined together with a minimum 1½" wide hot-air weld.

The above information represents a typical VersiFleece TPO Mechanically Attached Roofing System application. Refer to Versico's published specifications and details for more complete information.

# **VERSIFLEECE TPO**

## Certified Fabricated Accessories

Certified Fabricated Accessories (CFAs) are the only factory-fabricated TPO accessories that meet the stringent quality tolerances required to be included in a warranted Versico TPO roofing system.

## System Codes

- UL Class A and B ratings are available over various deck types
- FM codes are available over various deck types
- For code specifics, refer to Versico's Code Approval Guide

For code specifics, refer to Versico's Code Approval Guide.

## Quality Assurance

Versico Authorized Contractors have received training to install Versico's Mechanically Attached Roofing Systems.

## Inspection

Upon installation completion, and prior to the issuance of a system warranty, an inspection will be conducted by a Versico Field Service Representative.

## Warranty

Consult your Authorized Contractor or a Versico Independent Sales Representative for associated warranty charges.

This system, properly installed and inspected on a commercial project may receive:

### Total System Warranty Options

VersiFleece TPO Mechanically Attached						
	5-Year	10-Year	15-Year	20-Year	25-Year	30-Year
<b>100-Mil</b>	X	X	X			
<b>115-Mil</b>	X	X	X	X		
<b>135-Mil</b>	X	X	X	X	X	X

- 55-mph maximum peak gust wind speed coverage is standard. Additional coverage up to 72-mph is available.

For more specifics or on warranty programs, contact Versico.



Existing or New Deck Type	New Construction						Re-roofing		
	Steel	Plywood or OSB	Lt. Wt. Insulating Concrete	Structural Concrete	Wood Planks	Gypsum & Fibrous Cement	Smooth-Surface BUR	Gravel-Surfaced BUR	Existing Single-Ply
<b>Deck Overlayment Required</b>	Insulation	No	No	No	Insulation	Insulation	No	Insulation	No
<b>Recommended Insulations</b>	Versico Polyiso, Versico Recovery Board, DensDeck®, SECUROCK®, or Versico Recovery Board over Polystyrene						← Refer to New Construction		
<b>Insulation Attached By</b>	Versico fasteners and plates						← Refer to New Construction		
<b>Membrane Attached By</b>	HPVX Fasteners & Plates; HPV-XL Fasteners & Plates	HPVX Fasteners & Plates; HPV-XL Fasteners & Plates	Lt. Wt. Deck Fasteners/Plates	CD-10/ HPVX Plates; MP 14-10 Fasteners	HPVX Fasteners & Plates	Lt. Wt. Deck Fasteners/Plates	← Refer to New Construction		

FOR TEAR-OFF OPTIONS REFER TO NEW CONSTRUCTION ABOVE.  
For current code approvals and warranties, visit Versico's website or contact a design analyst.



## A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • [www.versico.com](http://www.versico.com)