



# VERSICO

## ROOFING SYSTEMS

### R-values Flat Polyiso

VersiCore® SecurShield®			
Size	LTTR*	PCS	4X8 SF
0.5	2.8	96	3072
1.0	5.7	48	1536
1.1	6.3	43	1376
1.2	6.8	40	1280
1.3	7.4	36	1152
1.4	8.0	34	1088
1.5	8.6	32	1024
1.6	9.1	30	960
1.7	9.7	28	896
1.75	10.0	27	864
1.8	10.3	26	832
1.9	10.8	25	800
2.0	11.4	24	768
2.1	12.0	22	704
2.2	12.6	21	672
2.3	13.2	20	640
2.4	13.8	20	640
2.5	14.4	19	608
2.6	15.0	18	576
2.7	15.6	17	544
2.8	16.2	17	544
2.9	16.8	16	512
3.0	17.4	16	512
3.1	18.0	15	480
3.2	18.6	15	480
3.3	19.2	14	448
3.4	19.9	14	448
3.5	20.5	13	416
3.6	21.1	13	416
3.7	21.7	12	384
3.8	22.3	12	384
3.9	23.0	12	384
4.0	23.6	12	384
4.3	25.5	11	352
4.5	26.8	10	320

\*LTTR = Long-Term Thermal Resistance

**BUILDING VALUE**

# Versico Loading

Slope	Panel Designation	Dimensions	BD FT Per Panel	PCS
1/8	AA	1/2" - 1"	12	64
	A	1" - 1 1/2"	20	38
	B	1 1/2" - 2"	28	26
	C	2" - 2 1/2"	36	20
	D	2 1/2" - 3"	44	16
	E	3" - 3 1/2"	52	14
	F	3 1/2" - 4"	60	12
	FF	4.0" - 4 1/2"	68	10
1/4	X	1/2" - 1 1/2"	16	48
	Y	1 1/2" - 2 1/2"	32	24
	Z	2 1/2" - 3 1/2"	48	16
	ZZ	3 1/2" - 4 1/2"	64	12
	G	1" - 2"	24	32
	H	2" - 3"	40	18
	I	3" - 4"	56	12
1/2	Q	1/2" - 2 1/2"	24	32
	QQ	2 1/2" - 4 1/2"	56	12
	XX	1" - 3"	32	24
3/16	JJ	1/2" - 1 1/4"	14	54
	KK	1 1/4" - 2"	26	28
	LL	2" - 2 3/4"	38	20
	MM	2 3/4" - 3 1/2"	50	14
	J	1" - 1 3/4"	22	34
	K	1 3/4" - 2 1/2"	34	22
	L	2 1/2" - 3 1/4"	46	16
	M	3 1/4" - 4"	58	12
3/8	SS	1/2" - 2"	20	38
	TT	2" - 3 1/2"	44	16
	S	1" - 2 1/2"	28	26
	T	2 1/2" - 4"	52	14
1/16	1	1/2" - 3/4"	10	76
	2	3/4" - 1"	14	54
	3	1" - 1 1/4"	18	42
	4	1 1/4" - 1 1/2"	22	34
	5	1 1/2" - 1 3/4"	26	28
	6	1 3/4" - 2"	30	24
	7	2" - 2 1/4"	34	22
	8	2 1/4" - 2 1/2"	38	20