CARLISLE
UNIVERSAL
SINGLE—PLY
SEALANT

WATER
CUT—OFF
MASTIC
XXXX

APPLICABLE
BONDING
ADHESIVE

TPO/PVC
ROOF
MEMBRANE

SURE—SEAL
TERMINATION BAR
FASTENED 6"
(15cm) MAX.

2

NEW GUTTER,
STRAPS &
FASTENERS (BY
OTHERS)

HP—PURLIN
FASTENER, REFER
TO SPECS

EXISTING GUTTER
(REMOVE)

RETAINING
BAR IN LIEU
OF
SURE—SEAL
TERMINATION
BAR TO AVOID
OVERSPILLING

CARLISLE
UNIVERSAL
SINGLE—PLY
SEALANT

2

NOTES:

1. FASTENING OF METAL
   TERMINATION BAR OR
   RETAINING BAR MUST
   PROVIDE CONSTANT
   COMPRESSION ON WATER
   CUT—OFF MASTIC.

2. ALLOW MEMBRANE SHEET TO
   EXTEND 1/2" (1.5cm)
   MINIMUM BELOW THE
   TERMINATION BAR.

3. REFER TO MR Z1.1 & MR
   Z1.2 AT THE END OF THIS
   SECTION.

GUTTER WITH
RETENTION BAR

GUTTER WITH METAL BAR EDGE TERMINATION

|	
▦ POLYISOCYANURATE INSULATION	▬▬▬ ROOF MEMBRANE
▨ IN—FILL INSULATION	⊠ WOOD NAILER (BY OTHERS)
0	SEE DRAWING NOTE(S)

SHEET NO.

MRI T1.4