

SureMB Vented Base Sheet



Overview

Versico's Vented Base Sheet is a heavyweight venting base sheet constructed from a fiberglass mat coated with weathering-grade asphalt. The bottom surface is embedded with mineral granules and embossed with a brick/stone pattern.

Features and Benefits

- Provides venting of vapor beneath base ply
- Inorganic mat resists rotting

Installation

Versico's Vented Base Sheet is used as a venting base sheet over lightweight insulating concrete or gypsum decks. The Vented Base Sheet is attached using Versico Dual Prong Base Sheet Fastener.

REVIEW CURRENT VERSICO SPECIFICATIONS AND DETAILS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Specifications

- Width: 39³/₈"
- Length: 33'
- Roll Weight: 86 lbs
- Ft² per roll: 100
- Reinforcement: fiberglass

Ratings and Certifications

- UL Type G/2 coated cap or base-ply sheet
- ASTM D4897, Type II

Typical Properties and Characteristics

Physical Property	Typical
Tensile Strength (@ 77°F and 2 in./min.)	MD=67 lbf/in. CD=55 lbf/in.

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

LEED® Information

Pre-consumer Recycled Content	0%
Post-consumer Recycled Content	0%
Manufacturing Location	Naples, TX
Solar Reflectance Index	N/A

Packaging

Product	SureMB Vented Base Sheet
Size/Weight	39.38" x 33'/86 lbs
Actual Coverage	100 ft ²
Part Number	321630



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com