



**VersiFleece AC EPDM
VersiFleece AC TPO
VersiFleece KEE HP**

Hot Mopped Adhered Roofing System

Code Approval Guide

November 2025

Table of Contents

UL Approvals:

Non-Combustible - ANSI UL - Class A.....	2
Combustible - ANSI UL - Class A.....	3

Existing UL Rating Retained:

Combustible and Non-Combustible.....	4
--------------------------------------	---

Mechanically Fastened - Recover

Recover on Steel Decking.....	4
-------------------------------	---

FM Approvals:

Securock New Construction.....	5-6
Securock Recover.....	7
DensDeck Prime New Construction.....	8-9
DensDeck Prime Recover.....	10
Recovery Board New Construction.....	11

Reference Notes.....	12
-----------------------------	-----------

Underwriter Laboratories
Hot Mopped (Asphalt) Adhered Roofing System

Non-Combustible- ANSI/UL 790 Spread of Flame Test- Class A

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

System ID	Deck Type	Insulation/Base	Cover Board	Maximum Slope		
				VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
1	Non-Combustible	Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/4" SECUROCK® Gypsum-Fiber Roof Board	2"	1"	Unlimited
2		Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/4" DensDeck Prime Roof Board	2"	1"	Unlimited
3		Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/2" Recovery Board	2"	1"	2"
4		One or more layers of the Versico Type G2 base sheet, hot mopped or mechanically fastened.	N/A	2"	1"	2"
5	Precast concrete with grouted joints	N/A	N/A	2"	1"	2"
6	Structural (poured-in-place) concrete	N/A	N/A	2"	1"	2"

Underwriter Laboratories
Hot Mopped (Asphalt) Adhered Roofing System

Combustible (1)- ANSI/UL 790 Spread of Flame Test- Class A

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

System ID	Thermal Barrier/Base Sheet	Insulation	Cover Board	Maximum Slope		
				VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
Combustible (1) - ANSI/UL 790 Spread of Flame Test-Class A						
1	N/A	Any UL Classified Versico Polyisocyanurate Insulation, any combination, any thickness.	Minimum 1/4" SECUROCK® Gypsum Fiber Roof Board (2)	2"	1"	3"
2	N/A	Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 3/8" SECUROCK® Gypsum Fiber Roof Board (2)	2"	1"	2"
3	N/A	Any UL Classified Insulation, any thickness (OPTIONAL)	Minimum 1/4" DensDeck Prime Roof Board (2)	2"	1"	Unlimited

Underwriter Laboratories
Hot Mopped (Asphalt) Adhered Roofing System

**Existing UL Rating Retained - Non-Combustible or Combustible
(Directly over existing Class A, B or C)**

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Non-Combustible: Steel; St. Concrete; Gypsum; Tectum (Min. 2" thick)

Combustible: 7/16-in. (minimum) thick non-veneer APA-rated sheathing (oriented strand board panels, structural particleboard panels, composite panels or waferboard panels); 15/32-in. (minimum) thick plywood 3/4 in. (minimum) wood; Tectum (less than 2" thick)

System ID	Deck Type	Insulation	Cover Board	Maximum Slope		
				VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
1	Combustible or Non-Combustible	Smooth Asphalt BUR (Type III or IV Asphalt)	N/A	1/2"	1/2"	1/2"
2		Mineral Surfaced Cap Sheet	N/A	1/2"	1/2"	1/2"
3		Modified Bitumen	N/A	1/2"	1/2"	1/2"

Mechanically Fastened Membrane - Recover

Membrane Width	Spacing	Rating	Min. 22 Gauge Grade C Steel (33 ksi)		
			VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
10 Feet	6"	1-105	138293-0-0	138702-0-0	N/A

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Securock- New Construction

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: DASH = Flexible DASH and Flexible DASH Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
FM Approved	Loose laid	Min. 1/4" Securock	12 (2.66 sq. ft)	1-75	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	10 (3.2 sq. ft)	1-90	-	-	389427-0-0
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/4" Securock	10 (3.2 sq. ft) SecurFAST Plate	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 5/8" Securock	8 (4 sq. ft) SecurFAST Plate	1-90	-	-	-
FM Approved	Loose laid	Min. 5/8" Securock	8 (4 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" Securock	8 (4 sq. ft) SecurFAST Plate	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" Securock	6 (5.33 sq. ft) SecurFAST Plate	1-75	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 5/8" Securock	6 (5.33 sq. ft) SecurFAST Plate	1-90	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	20 (1.6 sq. ft)	1-150	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	32 (1 sq. ft)	1-270	-	-	375702-0-0
Min. 1-1/2" VersiCore Polyiso	10 (3.2 sq. ft.)	Min. 1/4" Securock	6" ribbons of DASH	1-90	-	-	-
Min. 2" VersiCore Polyiso	8 (4 sq. ft.)	Min. 1/4" Securock	12" ribbons of DASH	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	18 (1.8 sq. ft.)	Min. 1/4" Securock	6" ribbons of DASH	1-105	-	-	-
Min. 1-1/2" VersiCore Polyiso	24 (1.33 sq. ft.)	Min. 1/4" Securock	4" ribbons of DASH	1-165	-	-	-
Min. 1/2" DensDeck Prime or 5/8" Securock	16 (2 sq. ft.)	Min. 1/4" Securock over 1-1/2" VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Steel Deck (Min. 22-Gauge) with VapAir Seal 725TR and Cav-Grip 3V or 702 Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" VersiCore Polyiso	DASH - Rig Splatter	1-135	-	-	-
Steel Deck (Min. 22-Gauge) with SureMB 70 SA and Cav-Grip 3V Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" VersiCore Polyiso	6" ribbons of DASH	1-135	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Securock- New Construction

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: DASH = Flexible DASH and Flexible DASH Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Steel Deck (Min. 22-Gauge) with SureMB 90 TG or 120 TG Base Torch Applied							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	Min. 1/4" Securock over Min. 1-1/2" VersiCore Polyiso	6" ribbons of DASH	1-135	-	-	-
Concrete Deck							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" Securock	12" ribbons of DASH	1-270	-	-	-
Min. 1/2" VersiCore Polyiso	Hot Asphalt	Min. 1/4" Securock	Hot Asphalt	1-270	-	-	-
Concrete Deck with VapAir Seal 725TR and CAV-GRIP 3V							
Min. 1-1/2" VersiCore Polyiso	Full-Coverage DASH	Min. 1/4" Securock	12" ribbons of DASH	1-255	-	-	-
Concrete Deck with SureMB 70 SA with CAV-GRIP 3V Primer							
Min. 1-1/2" VersiCore Polyiso	Full-Coverage DASH	Min. 1/4" Securock	12" ribbons of DASH	1-255	-	-	-
Concrete Deck with SureMB 90TG and 120TG Base Torch Applied/Cut-Back Asphalt Primer							
Min. 1-1/2" VersiCore Polyiso	Full-Coverage DASH	Min. 1/4" Securock	12" ribbons of DASH	1-255	-	-	-
Min. 1-1/2" VersiCore Polyiso	Hot Asphalt	Min. 1/2" Securock	Hot Asphalt	1-270	-	-	483488-0-0
Gypsum Deck Tear-Off							
Min. 1-1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" Securock	12" ribbons of DASH	1-90	-	-	-
(Celcore) Cellular Lightweight Insulating Concrete Over Steel Decking (Min. 22 Gauge)							
FM Approved	Loose laid	Min. 1/4" Securock	12 (2.67 sq. ft)	1-75	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	10 (3.2 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 5/8" Securock	8 (4 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	20 (1.6 sq. ft)	1-150	-	-	-
FM Approved	Loose laid	Min. 1/2" Securock	32 (1 sq. ft)	1-255	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Securock- Recover

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: DASH = Flexible DASH and Flexible DASH Dual Tank

Base Insulation Layer	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Concrete Deck							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" Securock	12" ribbons of DASH	1-90	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing Smooth Asphalt BUR or Modified Bitumen was FM Approved at the time of insulation.

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

DensDeck Prime- New Construction

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: DASH = Flexible DASH and Flexible DASH Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
FM Approved	Loose laid	Min. 1/4" DensDeck Prime	12 (2.67 sq. ft)	1-90	106651-0-0	-	-
FM Approved	Loose laid	Min. 1/2" DensDeck Prime	10 (3.2 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	5/8" DensDeck Prime	8 (4 sq. ft)	1-90	106648-0-0	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" DensDeck Prime	8 (4 sq.ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/4" DensDeck Prime	18 (1.8 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" DensDeck Prime	18 (1.8 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" DensDeck Prime	20 (1.6 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" DensDeck Prime	32 (1 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" DensDeck Prime	32 (1 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 1/2" DensDeck Prime	32 (1 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	10 (3.2 sq. ft.)	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	-	-	-
Min. 2" VersiCore Polyiso	8 (4 sq. ft.)	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	188315-0-0	189734-0-0	375582-0-0
Min. 1-1/2" VersiCore Polyiso	18 (1.8 sq. ft.)	Min. 1/4" DensDeck Prime	6" ribbons of DASH	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	24 (1.33 sq. ft.)	Min. 1/4" DensDeck Prime	4" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	16 (2 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Steel Deck with VapAir Seal 725 TR and CAV-GRIP 3V or 702 Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	DASH - Rig Splatter	1-135	-	-	-
Steel Deck with SureMB 70 SA and CAV-GRIP 3V Primer							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	6" ribbons of DASH	1-135	-	-	-
Steel Deck with SureMB 90TG or 120TG Base Torch Applied							
Min. 1/2" DensDeck Prime or Securock	8 (4 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" DensDeck Prime or Securock	20 (1.6 sq. ft.)	1/4" DensDeck Prime over VersiCore Polyiso	6" ribbons of DASH	1-135	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

DensDeck Prime- New Construction

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: DASH = Flexible DASH and Flexible DASH Dual Tank

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Concrete Deck							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	-	-	-
Min. 1/2" VersiCore Polyiso	Hot Asphalt	Min. 1/4" DensDeck Prime	Hot Asphalt	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	Loose laid	Min. 5/8" DensDeck Prime	8 (4 sq.ft)	1-90	-	210494-0-0	-
Concrete Deck with VapAir Seal 725 TR and CAV-GRIP 3V / 702-LV / 702 Primer							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90 Cav-Grip 3V	-	-	-
				1-90 702-LV	-	-	-
				1-90 702	-	-	-
Concrete Deck with SureMB 70 SA and CAV-GRIP 3V Primer							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	-	-	-
Concrete Deck with SureMB 90TG and 120TG Base Torch Applied/Cut-Back Asphalt Primer							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	-	-	-
Gypsum Deck Tear-Off							
Min. 1-1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	-	-	-
Cellular Lightweight Insulating Concrete Over Steel Decking							
FM Approved	Loose laid	Min. 1/4" DensDeck Prime	12 (2.67 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 1/2" DensDeck Prime	10 (3.2 sq. ft)	1-90	-	-	-
FM Approved	Loose laid	Min. 5/8" DensDeck Prime	8 (4 sq. ft)	1-90	-	-	-

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

DensDeck Prime- Recover

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base and Top Layer Adhesive: DASH = Flexible DASH and Flexible DASH Dual Tank

Base Insulation Layer	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Concrete Deck							
Min. 1/2" VersiCore Polyiso	12" ribbons of DASH	Min. 1/4" DensDeck Prime	12" ribbons of DASH	1-90	-	-	-

Note: Recover approvals in this document are based on the following existing roofing system assumption - the existing Smooth Asphalt BUR or Modified Bitumen was FM Approved at the time of insulation.

FM Approvals
Hot Mopped (Asphalt) Adhered Roofing System

Recovery Board- New Construction

Membrane Type: VersiFleece AC Plus EPDM Membrane
VersiFleece AC TPO Membrane
VersiFleece KEE HP Membrane

Membrane Adhesive: Hot Asphalt

Base Insulation Layer (Max. thickness 36")	Base Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Top Insulation Layer	Top Layer Fastening (mechanically fastened see notes 3, 4 & 5)	Rating	VersiFleece AC EPDM	VersiFleece AC TPO	VersiFleece KEE HP
					RoofNAV Number		
Steel Deck (Min. 22-Gauge)							
FM Approved	Loose laid	Min. 1/2" Recovery Board	16 (2 sq. ft)	1-90	-	-	-
Min. 1-1/2" VersiCore Polyiso	16 (2 sq. ft.)	Min. 1/2" Recovery Board	Hot asphalt	1-90	-	325133-0-0	-
Concrete Deck							
Min. 1" VersiCore Polyiso	Hot Asphalt	Min. 1/2" Recovery Board	Hot Asphalt	1-300	-	292371-0-0	-
Min. 1" VersiCore Polyiso	Hot Asphalt	Min. 1/2" Recovery Board	Hot Asphalt	1-270	292289-0-0	-	-
Concrete Deck with SureMB 90 Base Ply Hot Asphalt attached/Cut-Back Asphalt Primer							
Min. 1" VersiCore Polyiso	Hot Asphalt	Min. 1/2" Recovery Board	Hot Asphalt	1-300	-	-	375598-0-0
Cellular Lightweight Insulating Concrete Over Steel Decking							
FM Approved	Loose laid	Min. 1/2" Recovery Board	16 (2 sq. ft)	1-90	-	-	-

Hot Mopped (Asphalt) Adhered Roofing System

Reference Notes

1. Any roof covering system listed for use over a combustible roof deck can be installed over a non-combustible roof deck and achieve the same classification.
2. All insulation joints must be staggered a minimum of 6 inches from the deck joints or from the insulation joints directly below.
3. HPV fastener/Insulation plate.
4. InsulTITE fastener/Insulation plate.
5. InsulTITE fastener/SecurFAST Insulation Fastening plate.

Versico Roofing Systems, a division of Carlisle Construction Materials LLC

800-992-7663

VersiFleece AC EPDM Membrane, VersiFleece AC TPO Membrane,
VersiFleece KEE HP Membrane and DASH are Trademarks
of Versico Roofing Systems, a division of Carlisle Construction Materials LLC
DensDeck Prime is a Trademark of Georgia-Pacific

The contents of this issue represent the applicable information available at the time of publication. The contents of older issues are no longer accurate due to subsequent changes.

2025 Copyright Versico Roofing Systems, a division of Carlisle Construction Materials LLC