



NOTES:

1. WHEN SPECIFIED, SURE-WHITE EPDM, SURE-WELD TPO, SURE-FLEX PVC, AND FleeceBACK TPO MEMBRANE MAY BE ADHERED DIRECT WITH APPLICABLE ADHESIVE, REFER TO CARLISE SPECIFICATIONS.
2. APPLY EPDM PRIMER TO THE METAL FLANGE AND MEMBRANE SURFACE PRIOR TO INSTALLING QUICK APPLIED UNCURED EPDM FLASHING.
3. AS AN OPTION TO THERMOPLASTIC NON-REINFORCED MEMBRANE FLASHING, PRE-FABRICATED SPLIT PIPE SEAL MAY BE USED.

DIMENSIONS		cm	
(A)	3"	7.5	MIN.
(B)	2"	5	MIN.
(C)	1/2"	1.5	MIN.

FREQUENCY OF VENTS		
TYPE OF SUBSTRATE	NO. OF VENTS	MAX. AREA PER VENT
CELLULAR OR PERLITE LIGHTWEIGHT INSULATING CONCRETE	1	2,000 S.F. (186M²)

MEMBRANE

APPROVED SUBSTRATE

0

SEE NOTE(S)

ONE-WAY PRESSURE RELIEF VENT

For additional information, refer to Specifications

SU

DETAIL NO.  
G-04B