

## NOTES:


- REFER TO TABLES ON [SHEETS ATTACHMENT 1–2](#) FOR DETAILED INSPECTION, CLEANING AND PRIMING FOR DIFFERENT MATERIALS WITHIN THE FLASHING AREAS.
- DETAIL NOT FOR USE ON WARRANTY PROJECTS EXCEEDING 20-YEARS. UNLESS OTHERWISE SPECIFIED.
- PROPERLY FILL THE JOINTS, VOIDS AND CRACKS ENSURING PROPER SEAL AGAINST WATER MIGRATION.
- APPLICABLE SEAM DETAILS:
  - EPDM: [U-2A & U-2A.1](#)
  - TPO/PVC/KEE: [U-2A](#)

DIMENSIONS	cm	
(A)	3"	7.5 MIN.
(B)	2–3"	5–7.5 MIN.
(C)	AS REQUIRED DEPENDING ON SUBSTRATE, BUT MIN. 4" (10cm).	

	ROOF MEMBRANE
	LIQUISEAL Flashing Fleece
	LIQUISEAL Liquid Flashing Resin
	SEE NOTE(S)

MEMBRANE TIE-IN WITH EXISTING ROOF OVER CONCRETE DECK

For additional information, refer to Specifications



DETAIL NO.

LF-13.3

LIQUID FLASHING