

MARKETING ANNOUNCEMENT

Authorized Applicator



EPDM-2017-11 20" Pressure-Sensitive Cured Flashing July 18, 2017

To: Carlisle SynTec Systems' Authorized Applicators

Carlisle SynTec Systems is pleased to introduce its 20" Pressure-Sensitive Cured Flashing. Featuring a monolithic 20 inches of SecurTAPE™, this productivity-boosting accessory can be used to complete a variety of curb and pipe flashing details. 20" Pressure-Sensitive Cured Flashing will replace Carlisle's 20" Fully Pressure-Sensitive Curb Flashing, which has been discontinued.

Carlisle 20" Pressure-Sensitive Cured Flashing	
Product Code	329385 (previously 315839)
Stocking Location	Carlisle, PA and Greenville, IL
Packaging	1 roll per carton
Storage Requirements	Store between 60-90°F (15-32°C)
Product Notes	Cured, 60-mil Sure-Seal EPDM with 30-mil SecurTAPE 1-year shelf life Coat curbs covered with Polyiso insulation with EPDM Primer Poly release film is slit 6" in from the edge Weight per carton is 50 lbs

Using 20" Pressure-Sensitive Cured Flashing significantly improves the ease of completing the EPDM target splice under the Sure-Seal EPDM Pipe Boot when installing 30-year systems. Simply clean and prime the deck membrane, cut the 20" flashing to length, peel the release liner, stick the flashing in place, roll, and seal the edges with Lap Sealant. 20" Pressure-Sensitive Cured Flashing is also ideal for use as a target splice when installing MF-8A and MF-8B pipe details on mechanically fastened roof systems. Additional membrane securement required around pipes can now be overlaid with a single piece of flashing instead of four individual pieces.

If you have any questions or for more information, please contact your local manufacturer's representative or distributor.

Sincerely,

Ronald L. Goodman
EPDM Marketing Manager