




## Ballasted Systems



### Typical Applications

- 1 Approved ballast
- 2 VersiGard® EPDM with Quick-Applied Tape (QAT)
- 3 Versico Approved insulation
- 4 Approved roof deck

## VersiGard Reinforced and Non-Reinforced 25 – 30 year Total System Warranties\*

### 1. Approved Ballast:

1.5" nom. rounded water-worn gravel (ASTM C136 or D448)  
Crushed stone with HP Protective Mat  
Minimum 18-psf pavers  
2' x 2' x 2" pavers (maximum 80 lbs per unit)

### 2. Membrane:

45-mil VersiGard EPDM (25-year max.)  
60-mil VersiGard Non-Reinforced EPDM  
90-mil VersiGard Non-Reinforced EPDM

### 3. Versico Approved Insulation (loose-laid):

VersiCore® Polyisocyanurate  
SecurShield® Polyisocyanurate  
Insulfoam EPS  
Recovery Board (with acceptable insulation)  
XPS

### 4. Vapor Barrier (optional for new or tear-off only):

VapAir Seal™ 725TR  
VapAir Seal MD  
SureMB 90/120TG Base  
SureMB 90 Base Ply  
Polyethylene (by others)  
Other

### 5. Thermal Barrier (optional for new or tear-off only, not for use directly over concrete decks):

DensDeck®/DensDeck Prime  
SECUROCK® Gypsum Fiber  
Other

### 6. Deck:

22-gauge or heavier steel  
Structural concrete  
Wood plank  
Gypsum  
½" Plywood  
Lightweight insulating concrete  
Cementitious wood fiber

### 7. Metal Edging:

Shop-fabricated metal  
Versico VersiTrim™  
Metal by others

### 9. Construction Type:

New Construction  
Complete Tear-off

### 10. Slope:

2" per foot maximum.

### 8. Applicable Details:

VGB-1.1, VGC-1.2A, VGC-1.3, VGC-1.6, VGC-2.1A, VGC-2.2A, VGC-2.3, VGC-2.4, VGC-3.1, VGC-3.2, VGC-3.3, VGC-5.1, VGC-5.2, VGC-5.3, VGC-5.4, VGC-6.1, VGC-6.2, VGC-6.3, VGC-6.4, VGC-6.5, VGC-8.1A, VGC-8.3, VGC-8.3A, VGC-9.0A, VGC-9.0B, VGC-12.1, VGC-12.2, VGC-13.1, VGC-13.2, VGC-13.3, VGC-13.4, VGC-13.5, VGC-13.6, VGC-13.7, VGC-15.1, VGC-15.2, VGC-15.3, VGC-15.4A, VGC-15.7A, VGC-16.1A, VGC-16.2A, VGC-18.1, VGC-20.1, VGC-20.2, VGC-22, VGC-24, VGC-30.

\*Buildings up to 100' tall with 55-mph wind speed coverage. Projects requiring warranty wind speeds greater than 55-mph should be reviewed by a Versico representative. All products must be supplied by Versico to be included in the warranty coverage. All roof systems can only be accepted upon inspection by a Versico Field Service Representative. Versico reserves the right to change or enhance any of the above components due to specific or unique project conditions. The intent of this document is to verify the proposed roof assembly meets the requested warranty. Versico is not responsible for local and state building code requirements, and any discrepancy should be clarified by the design professional of record. Refer to Versico's most currently published specifications and details for additional information.

NOTE: No coverboards are to be used in a Ballasted System



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com

©2023 Versico. 12.22.23  
VE-7819 - VersiGard EPDM Ballast  
25-30 Year Warranty Submittal Sheet

VersiGard, VersiCore, VersiTrim and the Versico logo are trademarks of Versico. SecurShield and VapAir Seal are trademarks of Carlisle Construction Materials, LLC. DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC. SECUROCK is a trademark of USG Corporation or its subsidiaries or affiliates.