

VacuSeal™ Sealant Tape



Overview

Versico's VacuSeal Sealant Tape is a premier elastomeric butyl rubber sealant used with termination bar to secure and seal compression-type flashing terminations for the VacuSeal Vent Secured Roofing System. This product is extruded on silicone-coated paper for easy application.

Features and Benefits

- Superior adhesive strength
- Withstands extreme temperatures
- Resistant to UV light
- Available in rolls of 2.5" x 20'

Installation

Apply Sealant Tape to surface directly from roll. Press tape through the silicone release paper with a smooth, even hand motion.

REVIEW CURRENT VERSICO SPECIFICATIONS AND DETAILS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Precautions

- Surface preparation: All surfaces to be sealed should be free of dust, dirt, oil, and moisture before applying sealant.
- For best results, apply in dry conditions above 40°F (4°C).

Typical Properties and Characteristics

| | |
|-------------|---------------------------------------|
| Roll Width | 2.5" |
| Roll Length | 20' |
| Packaging | 6 rolls per case, 60 cases per pallet |
| Material | Elastomeric butyl rubber |
| Color | Gray |

| Tests | Test Method | Results |
|--------------------------------------|-------------|---------------------------------|
| Specific Gravity, lb./gal | ASTM D792 | 15 lbs./gal |
| Low Temperature Flexibility | ASTM C765 | No loss of adhesion or cracking |
| Weight Loss after Heat Aging | ASTM C771 | .13 No blisters |
| Oil Migration/Plasticizer Bleed-Out | ASTM C772 | .21" first paper |
| Softness mm. penetration | ASTM C782 | 6.47 mm |
| Tensile Adhesive Strength, lb. force | ASTM C907 | 16.45 psi MOF: Cohesive |
| Yield Strength, lb. force | ASTM C908 | 10.705 psi |

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com