

EPDM

System Warranty Availability

Membrane Attachment Method	Membrane Type	Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed	Maximum Hail Diameter	Accidental Puncture
Adhered	VersiGard Black (Non-Reinforced)	45-mil	15 YR	90 mph	N/A	N/A
		60-mil	25 YR	120 mph	1 inch	N/A
		90-mil	30 YR	120 mph	2 inch	32 hrs
	VersiGard Black (Reinforced)	45-mil	15 YR	90 mph	N/A	8 hrs
		60-mil	20 YR	120 mph	1 inch	16 hrs
		75-mil	30 YR	120 mph	2 inch	32 hrs
	VersiGard White (Non-Reinforced)	60-mil	25 YR	120 mph	1 inch	N/A
		90-mil	30 YR	120 mph	2 inch	32 hrs
Quick-Applied Sheet	VersiGard Black QA EPDM (Non-Reinforced)	60-mil	20 YR	100 mph	1 inch	N/A
	VersiGard White QA EPDM	60-mil	20 YR	100 mph	1 inch	N/A
	VersiGard Black QA EPDM (Reinforced)	60-mil	20 YR	100 mph	1 inch	16 hrs
Adhered with RapidLock	VersiFleece RL EPDM	115-mil	20 YR	90 mph	2 inch	16 hrs
		145-mil	30 YR	120 mph	3 inch	32 hrs
Ballasted	VersiGard Black EPDM (Non-Reinforced)	45-mil	25 YR	80 mph	1 inch	N/A
		60-mil	30 YR	80 mph	2 inch	N/A
		90-mil	30 YR	80 mph	3 inch	N/A
Mechanically Attached	VersiGard Black EPDM (Reinforced)	45-mil	15 YR	90 mph	N/A	8 hrs
		60-mil	20 YR	90 mph	N/A	16 hrs
		75-mil	30 YR	90 mph	N/A	32 hrs
	VersiFleece AC EPDM (Black)	100-mil	15 YR	72 mph	N/A	8 hrs
		115-mil	15 YR	72 mph	N/A	16 hrs
		145-mil	15 YR	72 mph	N/A	32 hrs

Refer to Versico's EPDM or VersiFleece Specification and Details for required design information for various warranty durations.

Hail coverage requires the use of an approved, adhered cover board: SecurShield HD or HD Plus, SecurShield HD Composite, DuraFaceR Composite, DuraStorm VSH, min. ½" thick DensDeck Prime or DensDeck StormX or min. ½" thick SECUROCK. Versico's Accidental Puncture Warranty covers labor hours and material used during the repair. Maximum labor and material hours are dependent upon system design. Refer to the above column for coverage.



TPO

System Warranty Availability

Membrane Attachment Method	Membrane Type	Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed	Maximum Hail Diameter	Accidental Puncture
Adhered	VersiWeld or VersiWeld HS (High Slope)	45-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	120 mph	1 inch	N/A
		80-mil	30 YR	120 mph	2 inch	16 hrs
	VersiWeld HS (Special Color TPO)	60-mil	20 YR	120 mph	1 inch	N/A
		80-mil	20 YR	120 mph	2 inch	16 hrs
Quick-Applied Sheet	VersiWeld QA TPO	60-mil	20 YR	100 mph	1 inch	N/A
		80-mil	30 YR	100 mph	2 inch	16 hrs
Adhered with Flexible DASH	VersiFleece TPO (VersiWeld)	100-mil	15 YR	120 mph	1 inch	8 hrs
		115-mil	25 YR	120 mph	2 inch	16 hrs
		135-mil	30 YR	120 mph	3 inch	32 hrs
	VersiFleece TPO (VersiWeld Special Color)	115-mil	20 YR	120 mph	2 inch	16 hrs
Adhered with Asphalt	VersiFleece AC TPO (VersiWeld)	120-mil	15 YR	90 mph	1 inch	N/A
		135-mil	20 YR	90 mph	2 inch	16 hrs
		155-mil	25 YR	90 mph	2 inch	32 hrs
Adhered with RapidLock	VersiFleece RL TPO (VersiWeld)	115-mil	20 YR	90 mph	2 inch	16 hrs
		135-mil	30 YR	120 mph	3 inch	32 hrs
Mechanically Attached	VersiWeld	45-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	90 mph	N/A	N/A
		80-mil	30 YR	90 mph	N/A	16 hrs
	VersiFleece FR TPO (VersiWeld Fire Rated)	115-mil	15 YR	72 mph	N/A	16 hrs
Induction Welded	VersiWeld	45-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	90 mph	N/A	N/A
		80-mil	20 YR	90 mph	N/A	16 hrs

Refer to Versico's Thermoplastic (TPO/PVC/KEE HP) or VersiFleece Specification and Details for required design information for various warranty durations.

Hail coverage requires the use of an approved, adhered cover board: SecurShield HD or HD Plus, SecurShield HD Composite, DuraFaceR Composite, DuraStorm VSH, min. ½" thick DensDeck Prime or DensDeck StormX or min. ½" thick SECUROCK.

When adhering VersiFleece TPO using Flexible DASH in full coverage (or beads at 4" o.c.) an extra 4 man hours of Accidental Puncture and an extra 1" of Hail coverage may be available (to a max. of 3"). Versico's Accidental Puncture Warranty covers labor hours and material used during the repair. Maximum labor and material hours are dependent upon system design. Refer to the above column for coverage.

*Follow seam detail VFFR-2.1 to obtain hail warranty coverage.



PVC

System Warranty Availability

Membrane Attachment Method	Membrane Type	Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed	Maximum Hail Diameter	Accidental Puncture
Adhered	VersiFlex PVC	50-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	120 mph	1 inch	N/A
		80-mil	25 YR	120 mph	2 inch	16 hrs
	VersiFlex KEE HP	50-mil	20 YR	90 mph	N/A	N/A
		60-mil	25 YR	120 mph	1 inch	N/A
		80-mil	30 YR	120 mph	2 inch	16 hrs
Adhered with Flexible DASH	VersiFleece PVC (VersiFlex)	105-mil	15 YR	120 mph	1 inch	N/A
		115-mil	20 YR	120 mph	2 inch	16 hrs
		135-mil	25 YR	120 mph	3 inch	32 hrs
	VersiFleece KEE HP (VersiFlex)	105-mil	20 YR	120 mph	1 inch	N/A
		115-mil	25 YR	120 mph	2 inch	16 hrs
		135-mil	30 YR	120 mph	3 inch	32 hrs
Adhered with RapidLock	VersiFleece RL PVC (VersiFlex)	115-mil	20 YR	90 mph	2 inch	16 hrs
		135-mil	30 YR	120 mph	3 inch	32 hrs
Mechanically Attached	VersiFlex PVC	50-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	90 mph	N/A	N/A
		80-mil	25 YR	90 mph	N/A	16 hrs
	VersiFleece PVC (VersiFlex)	105-mil	15 YR	72 mph	N/A	N/A
		115-mil	15 YR	72 mph	N/A	16 hrs
		135-mil	15 YR	72 mph	N/A	32 hrs
	VersiFlex KEE HP	50-mil	20 YR	90 mph	N/A	N/A
		60-mil	25 YR	90 mph	N/A	N/A
		80-mil	30 YR	90 mph	N/A	16 hrs
	VersiFleece KEE HP (VersiFlex)	105-mil	15 YR	72 mph	N/A	N/A
		115-mil	15 YR	72 mph	N/A	16 hrs
		135-mil	15 YR	72 mph	N/A	32 hrs
Induction Welded	VersiFlex PVC	50-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	90 mph	N/A	N/A
		80-mil	20 YR	90 mph	N/A	16 hrs
	VersiFlex KEE HP	50-mil	15 YR	90 mph	N/A	N/A
		60-mil	20 YR	90 mph	N/A	N/A
		80-mil	20 YR	90 mph	N/A	16 hrs

Refer to Versico's Thermoplastic (TPO/PVC/KEE HP) or VersiFleece Specification and Details for required design information for various warranty durations.

Hail coverage requires the use of an approved, adhered cover board: SecurShield HD or HD Plus, SecurShield HD Composite, DuraFaceR Composite, DuraStorm VSH, min. ½" thick DensDeck Prime or DensDeck StormX or min. ½" thick SECUROCK.

When adhering VersiFleece PVC or KEE HP using Flexible DASH in full coverage (or beads at 4" o.c.) an extra 4 man hours of Accidental Puncture and an extra 1" of Hail coverage may be available (to a max. of 3"). Versico's Accidental Puncture Warranty covers labor hours and material used during the repair. Maximum labor and material hours are dependent upon system design. Refer to the above column for coverage.



Traditional Roof Garden Systems

Extensive/Shallow Systems Warranty Availability

Membrane Attachment Method	Membrane Type		Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed
Adhered	EPDM	VersiGard Black (Non-Reinforced)	60-mil	15 YR	55 mph
			90-mil	20 YR	55 mph
		VersiGard Black (Reinforced)	60-mil	15 YR	55 mph
			75-mil	20 YR	55 mph
		VersiGard White (Non-Reinforced)	60-mil	15 YR	55 mph
			90-mil	20 YR	55 mph
	TPO	VersiWeld	60-mil	15 YR	55 mph
			80-mil	20 YR	55 mph
	PVC	VersiFlex PVC	60-mil	15 YR	55 mph
			80-mil	20 YR	55 mph
	KEE HP	VersiFlex KEE HP	60-mil	15 YR	55 mph
			80-mil	20 YR	55 mph
Quick-Applied Sheet	EPDM	VersiGard Reinforced QA EPDM	60-mil	15 YR	55 mph
	TPO	VersiWeld QA TPO	60-mil	15 YR	55 mph
			80-mil	20 YR	55 mph
Adhered with Flexible DASH	TPO	VersiFleece TPO (VersiWeld)	115-mil	15 YR	55 mph
			145-mil	20 YR	55 mph
	PVC	VersiFleece PVC (VersiFlex)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
	KEE HP	VersiFleece KEE HP (VersiFlex)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
Adhered with Asphalt	TPO	VersiFleece AC TPO (VersiWeld)	135-mil	15 YR	55 mph
			155-mil	20 YR	55 mph
Adhered with RapidLock	EPDM	VersiFleece RL EPDM	115-mil	15 YR	55 mph
	TPO	VersiFleece RL TPO	115-mil	15 YR	55 mph

Note: Refer to Versico's Traditional Roof Garden Specification and Details for required design information for various warranty durations.



Traditional Roof Garden Systems

Semi-Intensive/Medium Systems Warranty Availability

Membrane Attachment Method	Membrane Type		Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed
Adhered	EPDM	VersiGard Black (Non-Reinforced)	90-mil	20 YR	55 mph
		VersiGard Black (Reinforced)	75-mil	15 YR	55 mph
		VersiGard White (Non-Reinforced)	90-mil	20 YR	55 mph
	TPO	VersiWeld TPO	80-mil	20 YR	55 mph
	PVC	VersiFlex PVC	80-mil	20 YR	55 mph
	KEE HP	VersiFlex KEE HP	80-mil	20 YR	55 mph
Adhered with Flexible DASH	TPO	VersiFleece TPO (VersiWeld)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
	PVC	VersiFleece PVC (VersiFlex)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
	KEE HP	VersiFleece KEE HP (VersiFlex)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
Adhered with Asphalt	TPO	VersiFleece AC TPO (VersiWeld)	135-mil	15 YR	55 mph
			155-mil	20 YR	55 mph
Adhered with RapidLock	EPDM	VersiFleece RL EPDM (VersiGard)	115-mil	15 YR	55 mph
	TPO	VersiFleece RL TPO (VersiWeld)	115-mil	15 YR	55 mph

Note: Refer to Versico's Traditional Roof Garden Specification and Details for required design information for various warranty durations.



Traditional Roof Garden Systems

Intensive/Deep Systems Warranty Availability

Membrane Attachment Method	Membrane Type		Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed
Adhered	EPDM	VersiGard Black (Non-Reinforced)	90-mil	20 YR	55 mph
		VersiGard White (Non-Reinforced)	90-mil	20 YR	55 mph
	TPO	VersiWeld TPO	80-mil	15 YR	55 mph
	PVC	VersiFlex PVC	80-mil	15 YR	55 mph
	KEE HP	VersiFlex KEE HP	80-mil	15 YR	55 mph
Adhered with Flexible DASH	TPO	VersiFleece TPO (VersiWeld)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
	PVC	VersiFleece PVC (VersiFlex)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
	KEE HP	VersiFleece KEE HP (VersiFlex)	115-mil	15 YR	55 mph
			135-mil	20 YR	55 mph
Adhered with Asphalt	TPO	VersiFleece TPO (VersiWeld)	135-mil	15 YR	55 mph
Adhered with RapidLock	EPDM	VersiFleece RL EPDM (VersiGard)	115-mil	15 YR	55 mph
	TPO	VersiFleece RL TPO (VersiWeld)	115-mil	15 YR	55 mph

Note: Refer to Versico's Traditional Roof Garden Specification and Details for required design information for various warranty durations.



Modular Roof Garden Systems

Warranty Availability

Membrane Attachment Method	Membrane Type		Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed
Adhered	EPDM	VersiGard Black (Non-Reinforced)	60-mil	20 YR	55 mph
			90-mil	20 YR	55 mph
		VersiGard Black (Reinforced)	60-mil	20 YR	55 mph
			75-mil	20 YR	55 mph
		VersiGard White (Non-Reinforced)	60-mil	20 YR	55 mph
			90-mil	20 YR	55 mph
	TPO	VersiWeld	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
	PVC	VersiFlex PVC	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
	KEE HP	VersiFlex KEE HP	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
Quick-Applied Sheet	EPDM	VersiGard QA (Reinforced)	60-mil	20 YR	55 mph
	TPO	VersiWeld QA TPO	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
Adhered with Flexible DASH	TPO	VersiFleece TPO (VersiWeld)	115-mil	20 YR	55 mph
			145-mil	20 YR	55 mph
	PVC	VersiFleece PVC (VersiFlex)	115-mil	20 YR	55 mph
			135-mil	20 YR	55 mph
	KEE HP	VersiFleece KEE HP (VersiFlex)	115-mil	20 YR	55 mph
			135-mil	20 YR	55 mph
Adhered with Asphalt	TPO	VersiFleece AC TPO (VersiWeld)	135-mil	20 YR	55 mph
			155-mil	20 YR	55 mph
Adhered with RapidLock	EPDM	VersiFleece RL EPDM	115-mil	20 YR	55 mph
	TPO	VersiFleece RL TPO	115-mil	20 YR	55 mph

Note: Refer to Versico's Modular Roof Garden Specification and Details for required design information for various warranty durations.



Paver Systems

Warranty Availability

Membrane Attachment Method	Membrane Type		Minimum Membrane Thickness	Maximum Warranty Duration	Maximum Warranty Wind Speed
Adhered	EPDM	VersiGard Black (Non-Reinforced)	60-mil	20 YR	55 mph
			90-mil	20 YR	55 mph
		VersiGard Black (Reinforced)	60-mil	20 YR	55 mph
			75-mil	20 YR	55 mph
		VersiGard White	60-mil	20 YR	55 mph
			90-mil	20 YR	55 mph
	TPO	VersiWeld	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
	PVC	VersiFlex PVC	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
	KEE HP	VersiFlex KEE HP	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
Quick-Applied Sheet	EPDM	VersiGard QA (Reinforced)	60-mil	20 YR	55 mph
	TPO	VersiWeld QA TPO	60-mil	20 YR	55 mph
			80-mil	20 YR	55 mph
Adhered with Flexible DASH	TPO	VersiFleece TPO (VersiWeld)	115-mil	20 YR	55 mph
			145-mil	20 YR	55 mph
	PVC	VersiFleece PVC (VersiFlex)	115-mil	20 YR	55 mph
			135-mil	20 YR	55 mph
	KEE HP	VersiFleece KEE HP (VersiFlex)	115-mil	20 YR	55 mph
			135-mil	20 YR	55 mph
Adhered with Asphalt	TPO	VersiFleece AC TPO (VersiWeld)	135-mil	20 YR	55 mph
			155-mil	20 YR	55 mph
Adhered with RapidLock	EPDM	VersiFleece RL EPDM	115-mil	20 YR	55 mph
	TPO	VersiFleece RL TPO	115-mil	20 YR	55 mph

Note: Refer to Versico’s Modular Roof Garden Specification and Details for required design information for various warranty durations.



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com