

# EPDM Productivity Checklist

Increase your productivity by taking advantage of Carlisle SynTec Systems' labor-saving products. Use this checklist as a guide.



## EPDM Membranes

- Wide Sheets for Fully Adhered Systems** – reduce seaming labor
  - 16.5'-wide no-fold sheets – great in cold weather
  - 20', 25', or 30'-wide folded sheets for wide-open projects
- Factory-Applied Tape™** – reduces labor required to complete a seam by 70%
- 6.5'-wide 60-mil Reinforced Sheets** – eliminate the need for 9" Pressure-Sensitive (PS) RUSS strip on mechanically fastened systems
- Pre-Kleened Sheets** – allows roller application of primer and eliminates the need for Weathered Membrane Cleaner
- SAT™** – eliminates adhesive application and waiting for flash-off

## Flashings

- Pre-cut PS Inside/Outside Corners and T-Joint Covers** – eliminate the need for field cutting
- Prefabricated PS Pourable Sealer Pockets** – eliminate the need for field-fabrication
- 20" PS Cured Flashing** – eliminates the need to apply bonding adhesive and waiting for flash-off
- PS Overlayment Strip for Stripping in Edge Metal** – eliminates the need for T-Joint Covers on 60-mil
- PS Overlayment Strip for Overlaying Seams** – eliminates the need for Lap Sealant and T-Joint Covers

## Bonding Adhesives and Sealants

- CAV-GRIP™ III Low-VOC Adhesive/Primer** – formula promotes tenacious adhesion and quick flash-off time in a wide range of temperatures. Ask about new spray cart options.
- CAV-PRIME – Pressurized Cylinder and Equipment Speed Application of Primer** – one-sided application, no waiting for flash-off
- One-Part Pourable Sealer** – eliminates the need to mix a two-component product

## Cover Boards

- SecurShield® HD Plus** – reduces fasteners by 50% (from 16 to 8) for an FM 1-90 uplift requirement
- SecurShield HD with ReadyFlash** – much lighter and easier to cut than gypsum-based cover boards and reduces flash-off time
- SECUROCK® and SecurFast™ Plates** – fewer fasteners required to achieve FM 1-90 wind uplift rating
  - ¼" 16 fasteners down to 10 38% reduction
  - ⅜" 16 fasteners down to 8 50% reduction
  - ½" 10 fasteners down to 8 20% reduction
  - ⅝" 8 fasteners down to 6 25% reduction
- SecurShield HD Composite** – reduces fasteners by 62% (from 16 to 6) for an FM 1-90 uplift requirement.

## Fasteners

- AccuTrac Kits** – stand-up tool enhances productivity up to 38%
- HP-ASAP Fasteners** – pre-assembled plate and screw eliminates handling of two separate parts

## Insulation Adhesives and Insulation

- Flexible FAST™** – eliminates pre-drilling into concrete decks
- ReadyFlash Polyiso** – reduce flash-off time using the "dark side"

## Air and Vapor Barriers

- VapAir Seal™ MD** – eliminates the need for gypsum cover boards on steel decks
- CAV-GRIP III Low-VOC Adhesive/Primer** – spray installation, quick setup time, no waiting for flash-off

## Metal Edging

- SecurEdge™ Snap-on Canted Fascia** – eliminate the need to strip in metal flanges