
Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

PVC Un-Tack

Chemical Family

Adhesive

Product Use

Cleaner

Restrictions on Use

For industrial use only.

Manufacturer Information

Carlisle SynTec

1285 Ritner Highway

Carlisle, PA 17013

USA

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Skin Irritation - Category 3

Eye Damage - Category 2A

Specific Target Organ Toxicity - Single Exposure - Category 3

Extremely Flammable Aerosol - Category 2

GHS Label Elements

Symbol(s)



Signal Word

Danger!

Hazard Statement(s)

May cause mild skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Contains gas under pressure; may explode if heated

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

Precautionary Statement(s)

Avoid breathing vapors. Use in a well-ventilated area.

IF INHALED: Call a doctor if you feel unwell. Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Take off contaminated clothing and wash before reuse. Wash skin with plenty of water. If skin irritation occurs: Get medical attention.

Potential Health Effects

Principal Routes of Exposure

Inhalation, skin absorption, eye contact

Acute Effects:

EYE: Contact with eyes may cause irritation. Direct contact with liquid or vapors may cause stinging, tearing, redness, swelling and eye damage.

SKIN: May cause skin irritation and/or dermatitis. Prolonged or repeated contact or exposure to vapors may cause redness, burning, and drying and cracking of skin.

INHALATION: Breathing high concentrations of vapors may cause irritation of the nose and throat or signs of nervous system depression (e.g., headache, nausea, drowsiness, dizziness, vomiting, loss of coordination and fatigue).

INGESTION: Ingestion may cause irritation of the digestive tract, nausea, vomiting, and signs of nervous system depression.

Chronic Effects

Aggravated Medical Conditions

Avoid repeated exposure. May cause blood damage. Repeated contact may cause allergic reactions in very susceptible persons.

Pre-existing eye, skin or respiratory disorders may be aggravated by exposure to this product.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| CAS | Component Name | Percent |
|---------|----------------|---------|
| 67-64-1 | Acetone | 92-100 |

Any remaining ingredients (to comprise 100% of the product) should be considered a proprietary blend of non-hazardous substances, or materials below threshold reporting limits.

Section 4 - FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance.

Eyes

Flush with plenty of cool water for at least 15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get immediate medical attention.

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

Skin

Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash affected areas thoroughly with mild soap. If skin irritation persists, get immediate medical attention.

Inhalation

Move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen and get immediate medical attention.

Ingestion

Do not induce vomiting seek immediate medical attention. If vomiting occurs, keep head lower than hips to prevent aspiration.

Note to Physicians

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemicals, foam. Water may be helpful in keeping adjacent containers cool; avoid spreading the liquid with water used for cooling. Water-based sprinkler systems may help contain larger fires.

Special Protective Equipment and firefighting procedures

Wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Special Hazards Arising from the Chemical

Closed containers may rupture if exposed to fire or extreme heat. May produce toxic fumes if burning.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective clothing and equipment, see Section 8. Remove all sources of ignition.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Methods and Materials for Containment and Cleaning Up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Other Information

None known.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from extremes of heat or cold. Keep in properly labeled containers.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Note: Any items listed in the above with workplace control parameters which are not listed in section 3 are below threshold reporting values.

REL - Recommended Exposure Limits

TLV - Threshold Limit Value

Component Exposure Limits

| | |
|------------|--------------|
| Acetone | 67-64-1 |
| ACGIH: | 250 ppm TLV |
| OSHA (US): | 1000 ppm PEL |

Engineering Controls

Ensure adequate ventilation, especially in confined areas.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Safety goggles or glasses, or full face shield.

Skin Protection

Protective gloves and impervious clothing. Consult the glove/clothing manufacturer for proper selection of materials.

Respiratory Protection

In operations where exposure limits are exceeded, use a NIOSH-approved respirator that has been selected by a technically qualified person for the specific work conditions.

Hygiene Practices

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

before re-use. Wash thoroughly after handling. When using, do not eat, drink or smoke.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------------------------|--------------------|--|-------------------|
| Appearance | Clear liquid | Upper Flammability/ Explosive Limit | 12.81 |
| Oxidizing Properties | No Data Available | Lower Flammability/ Explosive Limit | 2.60 |
| Odor | Solvent odor | Vapor Pressure mm Hg | Not Available |
| Odor Threshold | No Data Available | Vapor Density | Heavier than air |
| pH Value | No Data Available | Bulk Density (lb/gal) | 6.53 |
| Melting Point/ Freezing Point | No Data Available | VOC Content (g/L) | 0 |
| Boiling Point Range | 133.0 °F (56.1 °C) | VOC Less Water & Exempts (g/L) | 0 |
| Non-Volatile (wt%) | 0.00 | Specific Gravity g/l | 0.784 |
| Flash Point | -4.0 °F (-20.0 °C) | Auto-Ignition Temperature | No Data Available |
| Explosive Properties | No Data Available | Decomposition Temperature | No Data Available |
| Evaporation Rate | Faster than nBuAc | Partition Coefficient | No Data Available |
| Flammability (solids) | No Data Available | Viscosity | No Data Available |
| Solubility in Water | Insoluble | | |

Other Information

No additional information available.

Section 10 - STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions. Hazardous polymerization does not occur.

Possibility of Hazardous Reactions

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

None under normal conditions of use.

Conditions to Avoid

Keep away from open flames, hot surfaces, static electricity and sources of ignition. Avoid extremes of heat or cold.

Materials to Avoid

Incompatible with strong acids and bases, alkali metals, halogens, and strong oxidizing agents.

Hazardous Decomposition

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide, smoke, and other unidentified organic compounds may be formed during combustion.

Section 11 - TOXICOLOGICAL INFORMATION

Numerical Measures of Toxicity for Individual Components

Likely Routes of Exposure

Inhalation, skin absorption, eye contact.

Acute Toxicity

Oral

No data.

Skin

No data

Inhalation

No data.

Sensitization

Respiratory

No data.

Skin

No data.

Irritation

Skin

Category 3.

Mutagenicity

No data.

Reproductive Toxicity

No data.

Aspiration Hazard

No data.

Specific Target Organ Toxicity - Single Exposure

Category 3

Specific Target Organ Toxicity - Repeated Exposure

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

No data.

Chronic Toxicity / Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen. If no ingredients are listed below, then there are no known classifications.

| Component | IARC | NTP | OSHA |
|-----------|------|-----|------|
|-----------|------|-----|------|

Section 12 - ECOLOGICAL INFORMATION

The information and data for components are listed individually for areas of ecological consideration below.

Aquatic Toxicity

Acute and prolonged toxicity to fish: No Data Available

Acute toxicity to aquatic invertebrates: No Data Available

Environmental fate and pathways: No Data Available

Persistence and Degradability

No Data Available.

Mobility in Soil

No Data Available.

Bioaccumulative Potential

No Data Available.

Other Adverse Effects

No Data Available.

Section 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state, and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

Section 14 - TRANSPORT INFORMATION

The shipping classification in this section is meant as a guide to overall classification of the product. However, transportation classifications may be subject to change with changes in package size. Consult shipper requirements under 49 CFR, IATA and IMDG to assure regulatory compliance.

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

US DOT Information:

Shipping Name: CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.

Technical Name: (ACETONE, AIR)

Hazard Class: 2.1

UN/NA #: UN3501

Packing Group:

Placards:



ICAO / IATA Information:

No Data Available.

IMDG / IMO Information:

No Data Available.

Section 15 - REGULATORY INFORMATION

U.S. TSCA

Yes All components are listed or exempt.

Canada DSL

Yes All components are listed or exempt.

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

SARA Section 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Chemical Designation | CAS Number | Weight % |
|----------------------|------------|----------|
|----------------------|------------|----------|

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

| Chemical Designation | CAS Number | Weight % |
|----------------------|------------|----------|
|----------------------|------------|----------|

State Regulations

California Prop. 65

This product contains one or more chemicals known to the state of California to cause cancer and/or reproductive harm. Unless chemical names are listed below, these chemicals are present only in trace amounts. www.P65Warnings.ca.gov

| Chemical Designation | CAS Number |
|----------------------|------------|
|----------------------|------------|

Safety Data Sheet

Material Name: PVC Un-Tack

Product #:336090

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 3 Reactivity: 0B

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic Hazard

Summary of Changes

New SDS: April 24, 2020

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.