

VersiFlex™ PVC Outside Corners



Overview

VersiFlex PVC Outside Corners are pre-molded and are used for flashing outside corners on a variety of details. Installation is fast and easy with no cutting or stretching required. This product is available in white, gray and tan.

Versico's PVC Outside Corners are part of the Certified Fabricated Accessory (CFA) program. Certified Fabricated Accessories are the only factory-fabricated PVC accessories that meet the stringent quality tolerances required to be included in a Versico warranted roofing system.

Features and Benefits

- Pre-formed, multi-wave design allows wrapping outside corners that are out of square and not exactly 90 degrees
- Provide substantial labor savings compared to field-fabricating the flashing detail from non-reinforced flashing
- More consistent appearance than outside corners field-fabricated from flashing
- Non-reinforced PVC enhanced with KEE HP for superior performance
- Can be used on both PVC and KEE HP systems

Installation

1. Position the PVC Outside Corner and begin welding at the innermost corner point and work away from the corner.
2. Use the edge of the roller to crease the corner flashing into any membrane step-off for a proper seal.
3. Probe all welded edges of the corner once the material has been completely cooled to ensure watertight performance.

REVIEW CURRENT VERSICO SPECIFICATIONS AND DETAILS FOR SPECIFIC INSTALLATION REQUIREMENTS.

Precautions

- Store pre-molded corners in a cool, shaded area and cover with light-colored, breathable, waterproof tarpaulins. PVC Outside Corners or PVC membranes that have been exposed to the weather or contaminated with dirt must be prepared with PVC Membrane Cleaner prior to hot-air welding.

Typical Properties and Characteristics

| | |
|-----------|--|
| Thickness | 0.060" (1.52 mm) |
| Color | White, Gray and Tan |
| Packaging | 12/bag |
| Material | Injection molded non-reinforced KEE HP enhanced PVC flashing |

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

LEED® Information

| | |
|--------------------------------|-----------------------------------|
| Pre-consumer Recycled Content | 0% |
| Post-consumer Recycled Content | 0% |
| Manufacturing Location | Bloomington, IL |
| Solar Reflectance Index | White: 111 Gray: 43 Tan: 50 |



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • www.versico.com