

CARLISLE'S AUTHORIZED APPLICATORS MARKETING ANNOUNCEMENT

ID-2017-04

CAV-GRIP™ Low-VOC Adhesive/Primer

March 13, 2017

To: Carlisle SynTec Systems' Authorized Applicators

Carlisle SynTec Systems is pleased to announce that its CAV-GRIP Low-VOC Adhesive/Primer can now be used to adhere standard Sure-Weld® TPO membranes and all FleeceBACK® TPO, PVC, and EPDM membranes to vertical walls. CAV-GRIP provides the following benefits:

- Quick-drying, low-VOC formula
- Tenacious adhesive bond
- Meets VOC requirements in all 50 states
- No stirring required
- Can be used in temperatures as low as 25°F
- No fumes or odors
- Sets up quickly, no wait required for flash-off
- Minimizes installation time and increases productivity

CAV-GRIP is applied using a self-contained spray system that provides quick, even coverage and requires minimal cleanup and maintenance. The system consists of a #40 cylinder with a special attachment for the reusable spray gun and hose. Please note: #40 cylinders, spray guns, and hoses are each sold separately.

<u>Product Description</u>	<u>Product Code</u>	<u>Stocking Locations</u>
CAV-GRIP #40 Cylinder	305432	C, G, T, S
6' Hose	304302	C, G, T, S
12' Hose	304303	C, G, T, S
18' Hose	304304	C, G, T
Spray Gun (including nozzle)	307490	C, G, T, S
UN-TACK™ #8 Cylinder (gun and hose cleaner)	308607	C, S

C=Carlisle, G=Greenville, T=Tooele, S=Senatobia

Coverage rates: approx. 1,200-1,500 FT² (single-sided), approx. 600-750 FT² (double-sided)

The use of CAV-GRIP Low-VOC Adhesive/Primer with standard TPO on vertical walls is limited to maximum 20-year warranted systems. For additional installation information, please refer to the CAV-GRIP Product Data Sheet.

If you have any questions, please contact your Carlisle Manufacturer's Representative.

Sincerely,



Michael Puzdrak
TPO Product Development Manager



Austin Kulp
FleeceBACK Product Manager