

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

**Material Name**

Low-VOC PVC Step 2 Primer

**Synonyms**

Primer

**Chemical Family**

Primer, mixture

**Product Use**

Solvent primer

**Restrictions on Use**

For industrial use only.

**Manufacturer Information**

Carlisle SynTec

1285 Ritner Highway

Carlisle, PA 17013 USA

Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (Chemtrec)

---

### Section 2 - HAZARDS IDENTIFICATION

---

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Flammable Liquids - Category 3

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Skin Sensitization - Category 1A

Carcinogenicity - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 2 ( liver,kidneys )

**GHS Label Elements****Symbol(s)****Signal Word**

Warning

## Safety Data Sheet

**Material Name: Low-VOC PVC Step 2 Primer**

**Product #: 332652**

### **Hazard Statement(s)**

Flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause allergic skin reaction

Suspected of causing cancer

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

### **Precautionary Statement(s)**

#### **Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

#### **Response**

In case of fire: Use appropriate media to extinguish

IF exposed or concerned: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Specific treatment (see label)

#### **Storage**

Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

#### **Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

---

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

| CAS          | Component Name                              | Percent |
|--------------|---------------------------------------------|---------|
| 64742-89-8   | Solvent naphtha, petroleum, light aliphatic | 10-30   |
| Trade Secret | Isophorone Diisocyanate                     | 0.5-1.5 |
| 108-88-3     | Toluene                                     | 3-7     |
| Trade Secret | Chlorinated polypropylene                   | 0.1-1   |
| 98-56-6      | PCBTF                                       | 60-100  |
| Trade Secret | Isophorondiamine-isobutyraldimine           | 0.1-1   |

---

### Section 4 - FIRST AID MEASURES

---

#### Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

#### Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### Ingestion

If swallowed, get medical attention.

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

#### Most Important Symptoms/Effects

##### Acute

Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. May cause drowsiness or dizziness.

##### Delayed

May cause allergic skin reaction. Suspected of causing cancer. May cause liver and kidney damage.

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

### Note to Physicians

Contains: toluene.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### Extinguishing Media

#### Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide. Water may be ineffective.

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

### Special Hazards Arising from the Chemical

Flammable liquid and vapor.

### Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen

### Advice for firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

### Fire Fighting Measures

Move container from fire area if it can be done without risk.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Ventilate the area. Use non-sparking tools. Use clean non-sparking tools to collect absorbed material and place it into loosely-covered metal or plastic containers for later disposal. Large spills: Dike for later disposal. Prevent entry into waterways, sewers, basements, or confined areas.

### Environmental Precautions

Avoid release to the environment. Collect spillage.

---

## Section 7 - HANDLING AND STORAGE

---

### Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and ignition sources. When using do not smoke. Use non-sparking tools. Ground any equipment used in handling. Wash with plenty of soap and water. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static

## Safety Data Sheet

**Material Name: Low-VOC PVC Step 2 Primer**

**Product #: 332652**

discharge. Do not breathe gas, fumes, vapor, or spray. Contaminated work clothing should not be allowed out of the workplace.

### Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

Keep away from heat, sparks and flame. Do not cut, puncture, or weld on or near this container. Empty containers may contain product residue. Keep away from incompatible materials.

### Incompatible Materials

Strong oxidizing agents, acids, bases

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Component Exposure Limits

|                |                                                               |                              |
|----------------|---------------------------------------------------------------|------------------------------|
| <b>Toluene</b> | 108-88-3                                                      |                              |
| ACGIH:         | 20 ppm TWA                                                    |                              |
| NIOSH:         | 100 ppm TWA; 375 mg/m3 TWA                                    | 150 ppm STEL; 560 mg/m3 STEL |
|                | 500 ppm IDLH                                                  |                              |
| Europe:        | 50 ppm TWA; 192 mg/m3 TWA                                     | 100 ppm STEL; 384 mg/m3 STEL |
|                | Possibility of significant uptake through the skin            |                              |
| OSHA (US):     | 200 ppm TWA                                                   | 300 ppm Ceiling              |
| Mexico:        | 50 ppm TWA LMPE-PPT; 188 mg/m3 TWA LMPE-PPT                   |                              |
|                | Skin - potential for cutaneous absorption                     |                              |
|                |                                                               |                              |
| <b>PCBTF</b>   | 98-56-6                                                       |                              |
| ACGIH:         | 2.5 mg/m3 TWA as F (related to Fluorides)                     |                              |
| OSHA (US):     | 2.5 mg/m3 TWA as F; 2.5 mg/m3 TWA dust (related to Fluorides) |                              |
| Mexico:        | 2.5 mg/m3 TWA LMPE-PPT as F (related to Fluorides)            |                              |

### Biological limit value

There are no biological limit values for any of this product's components.

### Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

#### Skin Protection

Wear appropriate chemical resistant clothing. Wear protective shoes.

#### Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

#### Glove Recommendations

Wear appropriate chemical resistant gloves.

---

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

|                              |                           |                                               |                          |
|------------------------------|---------------------------|-----------------------------------------------|--------------------------|
| <b>Appearance</b>            | thin brown liquid         | <b>Physical State</b>                         | liquid                   |
| <b>Odor</b>                  | Naphthenic distillate     | <b>Color</b>                                  | Light brown              |
| <b>Odor Threshold</b>        | Not available             | <b>pH</b>                                     | Not available            |
| <b>Melting Point</b>         | -95 - -33 °C(-139 - 27°F) | <b>Boiling Point</b>                          | 111 - 139 °C(232 -282°F) |
| <b>Freezing point</b>        | Not available             | <b>Evaporation Rate</b>                       | 1.4                      |
| <b>Boiling Point Range</b>   | Not available             | <b>Flammability (solid, gas)</b>              | Not available            |
| <b>Autoignition</b>          | 246 °C(475°F)             | <b>Flash Point</b>                            | 4 °C(40°F)               |
| <b>Lower Explosive Limit</b> | 0.9                       | <b>Decomposition</b>                          | Not available            |
| <b>Upper Explosive Limit</b> | 10.5                      | <b>Vapor Pressure</b>                         | 7.4 mmHg                 |
| <b>Vapor Density (air=1)</b> | 5.7                       | <b>Specific Gravity (water=1)</b>             | Not available            |
| <b>Water Solubility</b>      | insoluble                 | <b>Partition coefficient: n-octanol/water</b> | Not available            |
| <b>Viscosity</b>             | <200 cps                  | <b>Solubility (Other)</b>                     | Not available            |
| <b>Density</b>               | 1.177                     | <b>VOC</b>                                    | <250 g/L                 |

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

---

### Section 10 - STABILITY AND REACTIVITY

---

#### Reactivity

No reactivity hazard is expected.

#### Chemical Stability

Stable under normal conditions of use.

#### Possibility of Hazardous Reactions

Will not polymerize.

#### Conditions to Avoid

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Take action to prevent static discharges. Avoid contact with incompatible materials.

#### Incompatible Materials

Strong oxidizing agents, acids, bases

#### Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

---

### Section 11 - TOXICOLOGICAL INFORMATION

---

#### Information on Likely Routes of Exposure

##### Inhalation

May cause drowsiness or dizziness.

##### Skin Contact

Causes skin irritation.

##### Eye Contact

Causes serious eye irritation.

##### Ingestion

No information on significant adverse effects.

#### Acute and Chronic Toxicity

##### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Oral LD50 Rat >2000 mg/kg

Dermal LD50 Rat >2000 mg/kg

Inhalation Rat >5000 ppm 1 hour

Isophorone Diisocyanate (Trade Secret)

Oral LD50 Rat >20000 mg/kg

Dermal LD50 Rabbit 4000 mg/kg

Inhalation LC50 Rat 5 mg/l 4 h

## Safety Data Sheet

**Material Name: Low-VOC PVC Step 2 Primer**

**Product #: 332652**

Toluene (108-88-3)

Oral LD50 >7000 mg/kg

Dermal LD50 12 - 14 g/kg

Inhalation LC50 30 mg/L

chlorinated homopolymer (Trade Secret)

Oral Rat 5000 mg/kg

PCBTF (98-56-6)

Oral LD50 Rat 13 g/kg

Dermal LD50 Rabbit >2 mL/kg

Inhalation LC50 Rat 33 mg/L 4 h

Isophorondiamine-isobutyraldimine (Trade Secret)

Oral Rat 4150 mg/kg [OECD Test Guideline 401]

Dermal Rat >5000 mg/kg [OECD Test Guideline 402]

### Immediate Effects

Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. May cause drowsiness or dizziness.

### Delayed Effects

May cause allergic skin reaction. Suspected of causing cancer. May cause liver and kidney damage.

### Irritation/Corrosivity Data

Causes skin and eye irritation.

### Respiratory Sensitization

No information available for the product.

### Dermal Sensitization

May cause allergic skin reaction.

### Component Carcinogenicity

|                |                                                                       |
|----------------|-----------------------------------------------------------------------|
| <b>Toluene</b> | 108-88-3                                                              |
| ACGIH:         | A4 - Not Classifiable as a Human Carcinogen                           |
| IARC:          | Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable)) |
| PCBTF          | 98-56-6                                                               |
| ACGIH:         | A4 - Not Classifiable as a Human Carcinogen (related to Fluorides)    |

### Germ Cell Mutagenicity

No information available for the product.

### Tumorigenic Data

No data available

### Reproductive Toxicity

No information available for the product.

## Safety Data Sheet

**Material Name:** Low-VOC PVC Step 2 Primer

**Product #:** 332652

**Specific Target Organ Toxicity - Single Exposure**

central nervous system

**Specific Target Organ Toxicity - Repeated Exposure**

Prolonged exposure may cause liver and kidney damage.

**Aspiration hazard**

No information available for the product.

**Medical Conditions Aggravated by Exposure**

May cause allergic skin reaction.

### Section 12 - ECOLOGICAL INFORMATION

**Component Analysis - Aquatic Toxicity**

|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Solvent naphtha, petroleum, light aliphatic</b> | 64742-89-8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Algae:                                             | EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Isophorone Diisocyanate</b>                     | Trade Secret                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Fish:                                              | LC50 96 h Oncorhynchus mykiss 9.22 mg/L                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Invertebrate:                                      | EC50 48 h Daphnia magna 6.14 mg/L IUCLID                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Toluene</b>                                     | 108-88-3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Fish:                                              | LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static] |
| Algae:                                             | EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA                                                                                                                                                                                                                                                                                                                                                                                                    |
| Invertebrate:                                      | EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

|               |                                          |
|---------------|------------------------------------------|
| PCBTF         | 98-56-6                                  |
| Invertebrate: | EC50 48 h Daphnia magna 3.68 mg/L IUCLID |

---

### Section 13 - DISPOSAL CONSIDERATIONS

---

#### Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

---

### Section 14 - TRANSPORT INFORMATION

---

#### US DOT Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN/NA #: UN1133

Packing Group: II

Required Label(s): 3

#### IATA Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

Required Label(s): 3

#### TDG Information:

Shipping Name: ADHESIVES

Hazard Class: 3

UN#: UN1133

Packing Group: II

---

### Section 15 - REGULATORY INFORMATION

---

#### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

|           |                              |
|-----------|------------------------------|
| Toluene   | 108-88-3                     |
| SARA 313: | 1 % de minimis concentration |

## Safety Data Sheet

**Material Name: Low-VOC PVC Step 2 Primer**

**Product #: 332652**

|           |                                                                         |
|-----------|-------------------------------------------------------------------------|
| CERCLA:   | 1000 lb final RQ; 454 kg final RQ                                       |
| TSCA 12b: | Section 4 , 1 % de minimus concentration (related to Hydrocarbons, C>4) |
| PCBTF     | 98-56-6                                                                 |
| TSCA 12b: | Section 4 , 1 % de minimus concentration                                |

**SARA Section 311/312 (40 CFR 370 Subparts B and C)**

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS      | CA  | MA  | MN  | NJ  | PA  |
|-----------|----------|-----|-----|-----|-----|-----|
| Toluene   | 108-88-3 | Yes | Yes | Yes | Yes | Yes |
| PCBTF     | 98-56-6  | Yes | No  | Yes | Yes | Yes |

**The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

|                |                                   |
|----------------|-----------------------------------|
| Toluene        | 108-88-3                          |
| Repro/Dev. Tox | developmental toxicity , 1/1/1991 |

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

|         |          |
|---------|----------|
| Toluene | 108-88-3 |
|         | 1 %      |

**Component Analysis - Inventory**

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | No        | No        | Yes            | No        | Yes | Yes | Yes |

**Isophorone Diisocyanate (Trade Secret)**

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | No        | No        | Yes            | No        | Yes | Yes | Yes |

## Safety Data Sheet

Material Name: Low-VOC PVC Step 2 Primer

Product #: 332652

### Toluene (108-88-3)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes |

### chlorinated homopolymer (Trade Secret)

| US  | CA  | EU | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX |
|-----|-----|----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|----|
| Yes | DSL | No | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | No |

### PCBTF (98-56-6)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|----|
| Yes | DSL | EIN | Yes | Yes | Yes       | Yes       | Yes            | No        | Yes | Yes | No |

### Isophorondiamine-isobutyraldimine (Trade Secret)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | No             | No        | Yes | Yes | No |

## Section 16 - OTHER INFORMATION

### HMIS Rating

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

### NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Summary of Changes

New SDS: 4/24/2015

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -

## Safety Data Sheet

**Material Name: Low-VOC PVC Step 2 Primer**

**Product #: 332652**

Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### Other Information

#### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.